

QNAP TVS-h1688X-W1250-32G 144TB (Seagate Ironwolf) 16-Bay TurboNAS (12 x 3.5 HDD + 4 x 2.5 SSD); SATA 6G; Intel Xeon W-1250 6 cores 12 threads 3.3 GHz (boost up to 4.7 GHz); 32GB DDR4 ECC RAM (max. 128GB); 4 x 2.5GbE; 2 x 10GBASE-T 10GbE; 2 x M.2 22110/ NAS Tower Ethernet LAN Black







Brand: ONAP

Product code: TVS-H1688X-W1250-32G/144TB-IW

Product name : TVS-h1688X-W1250-32G 144TB (Seagate Ironwolf) 16-Bay TurboNAS ($12 \times 3.5 \text{ HDD} + 4 \times 2.5 \text{ SSD}$); SATA 6G; Intel Xeon W-1250 6 cores 12 threads 3.3 GHz (boost up to 4.7 GHz); 32GB DDR4 ECC RAM (max. 128GB); 4×2.5 GbE; 2×10 GBASE-T 10GbE; 2×10 GBASE-T 20GbE; 2×10 GBASE-T 10GbE; 2×10 GBASE-T 10GBASE-T 10GBE; 2×10 GBASE-T 10GBE; 2×10 GBASE-T

- Attain quad-port Thunderbolt $^{\rm m}$ 3 connectivity by installing two QXP-T32P expansion cards in the PCle Gen 3 x4 slots
- Two 10GBASE-T and four 2.5GbE LAN ports accelerate virtualization, intensive file access, large backup/restoration tasks, and media transfer
- PCIe slots allow for installing 5/10/25/40GbE adapters, QM2 cards, or graphics cards to increase application performance
- 4K media playback and real-time transcoding; directly output videos to an HDMI display (up to 4K @30Hz)
- Supports virtual machines and containerized apps, centralized storage, backup, sharing, disaster recovery, and storage expansion
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud

Intel Xeon W-1250 6-core (3.3 GHz), Intel UHD Graphics P630, 4 x Long-DIMM DDR4, LCD, 6x USB 3.2 Gen 2, HDMI, 550 W

Storage		Design	
Storage drive interface *	Serial ATA II, Serial ATA III	Cable lock slot	✓
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Cable lock slot type	Kensington
Storage drive sizes supported	2.5,3.5,M.2 2	Performance	
Number of M.2 (M & B) slots		Type *	NAS
RAID support *		Backup function *	✓
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Backup features	Cloud, USB drive, iSCSI LUN
Online RAID migration	V	Buzzer	✓
Online RAID expansion	V	Multilingual support	✓
RAID rebuild	V	Noise level	25.8 dB
Hot-swap drive bays	· · · · · · · · · · · · · · · · · · ·	Third-party support	✓
Supported file systems	FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4	Snapshot	✓
Storage drives installed *	✓	Management protocols	SNMP
Total installed storage capacity *	144 TB	Web-based management	✓
Number of storage drives supported *	16	Share folder access right management	✓
Supported storage drive types *	HDD & SSD	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Auto-rebuild	V	Access Control List (ACL)	✓
Bad block scan	√	Reset button	✓
Processor		On/off switch	✓
Processor manufacturer *	Intel	Built-in BitTorrent client	✓
Processor family *	Intel® Xeon®	Built-in FTP server	✓
Processor model *	W-1250	Browser supported	Safari, Google Chrome, Internet Explorer, Mozilla Firefox
Processor frequency *	3.3 GHz		
	4.7 GHz	System log	✓
Processor boost frequency			
Processor boost frequency Processor cores	6	Hot spare	✓
' '		S.M.A.R.T. support	1
Processor cores	6	S.M.A.R.T. support Universal Plug and Play (UPnP)	√ √ √
Processor cores Processor threads	6 12	S.M.A.R.T. support	* * * * * * * * * * * * * * * * * * *
Processor cores Processor threads Processor cache	6 12 12 MB	S.M.A.R.T. support Universal Plug and Play (UPnP)	* * * * * * * * * *

Memory		Software	
Internal memory type DDR4 Maximum RAM supported 128 GB Memory slots 4 Internal memory * 32 GB Memory form factor UDIMM ECC	DDR4 128 GB 4 32 GB UDIMM	Software Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported Server operating systems supported Other operating systems supported Power Power Power supply location Power supply unit (PSU) capacity Power consumption (typical)	Server 2019
		Power consumption (sleep) AC input voltage Fan voltage	91.26 W 100 - 240 V 12 V
	* * * * * * * * * * * * * * * * * * *	Weight & dimensions Width * Depth * Height *	369.9 mm 319.8 mm 303.8 mm
Ports & interfaces		Packaging content	
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4	Cables included Power cables quantity Number of screws	AC, LAN (RJ-45) 1 72
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Processor special features	
HDMI ports quantity HDMI version Ethernet LAN (RJ-45) ports * PCI Express x4 (Gen 3.x) slots PCI Express x8 (Gen 3.x) slots	1 1.4b 6 2 1	Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64	× · · · · · · · · · · · · · · · · · · ·
Design		Intel Clear Video Technology	1
Chassis type * Cooling type * Product colour Number of fans Fan diameter Fan diameter 2 LED indicators Built-in display Display type	Tower Active Black 5 fan(s) 8 cm 9.7 cm HDD, LAN, Status, System, USB ✓	Intel Trusted Execution Technology Intel Virtualization Technology (VT-x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT) Operational conditions	1 1 1
		Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T)	0 - 40 °C 5 - 95% -20 - 70 °C

