QNAP TS-453BU NAS Rack (1U) Intel® Celeron® J3455 HDD QNAP Turbo System Aluminium, Black

Brand : QNAP

Product code: TS-453BU-2G-4TB-GLD

Product name : TS-453BU

4TB (Western Digital Gold), Intel Apollo Lake J3455 (1.5/2.3GHz), 2GB DDR3L, Gigabit LAN QNAP TS-453BU. Type: NAS. Chassis type: Rack (1U). Processor family: Intel® Celeron®, Processor model: J3455, Processor frequency: 1.5 GHz. Installed storage drive type: HDD. Operating system installed: QNAP Turbo System





| Storage | | Software | |
|---|---|---|--|
| Storage drive interface * RAID support * | Serial ATA III | Linux operating systems supported Mac compatibility | 4 |
| RAID support Image: Constraint of the systems RAID levels 0, 1, 5, 6, 10, 50, 60, JBOD Online RAID migration Image: Constraint of the systems Image: Constraint of the systems Image: Constraint of the systems Storage drives installed * Image: Constraint of the systems | 0, 1, 5, 6, 10, 50, 60, JBOD ✓ | Mac operating systems supported | Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| | Server operating systems supported | Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016 | |
| Number of storage drives supported | 4 | Power | |
| * Installed storage drive type * Supported storage drive types * Bad block scan | HDD HDD & SSD | Power supply location Power supply unit (PSU) capacity Number of power supply units | Built-in 250 W 1 |
| Processor | | Redundant power supply (RPS) support | × |
| Processor manufacturer * Intel Processor family * Intel® Celeron® Processor model * J3455 Processor frequency * 1.5 GHz Processor boost frequency 2.3 GHz | Intel® Celeron® J3455 | Power consumption (typical) Power consumption (HDD standby) AC input voltage AC input frequency Fan voltage | 31.5 W 21.3 W 100 - 240 V 50 - 60 Hz 12 V |
| Processor cores | 4 | Weight & dimensions | |
| Processor threads4Processor cache2 MBCPU configuration (max)1ECC supported by processor×PCI Express configurations1x2+2x1, 4x1 | 2 MB 1 X 1x2+2x1, 4x1 | Width * Depth * Height * Weight Package weight | 439 mm 499 mm 44 mm 6.53 kg 9.47 kg |
| PCI Express slots version | 2.0 Smart Cache | Packaging content | |
| rocessor cache type Smart Cache rocessor code SR2Z9 rocessor codename Apollo Lake | Cables included Quick installation guide | AC, LAN (RJ-45) ✔ | |
| Processor lithography | 14 nm | Processor special features | |
| Processor operating modes Processor package size Processor socket | 64-bit 24 x 31 mm BGA 1296 | Embedded options available Enhanced Intel SpeedStep Technology | 4 |
| Stepping Tjunction | B1 105 °C 10 W | Execute Disable Bit Idle States Intel 64 | 4 |

| Processor | | Processor special features | |
|---|---|---|------------------------------|
| On-board graphics card model | Intel [®] HD Graphics 500 | Intel Clear Video Technology | 1 |
| Maximum internal memory | 8 GB | Intel Enhanced Halt State | 1 |
| supported by processor | 0.00 | Intel Identity Protection Technology | 1.00 |
| Conflict-Free processor | ✓ | version | 1.00 |
| Memory | | Intel Rapid Storage Technology | × |
| Maximum RAM supported | 8 GB | Intel Secure Boot | 4 |
| Memory slots | 2 | Intel Secure Boot Technology version | 1.00 |
| Memory form factor | SO-DIMM | Intel Secure Key Technology version | 1.00 |
| Flash memory | 4096 MB | Intel Small Business Advantage | |
| Network | | (SBA) version | 0.00 |
| | | Intel Smart Connect Technology | × |
| Ethernet LAN * | | Intel Smart Connect Technology | 0.00 |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | version | 0.00 |
| Wi-Fi | × | Intel Smart Response Technology | 0.00 |
| DHCP client | 1 | version | |
| DHCP server | 4 | Intel Stable Image Platform Program (SIPP) | × |
| Jumbo frames support | 4 | Intel Stable Image Platform Program | |
| iSCSI support Wake on LAN ready | | (SIPP) version | 0.00 |
| Wake-on-LAN ready | | Intel Trusted Execution Technology | × |
| Supported network protocols | CIFS/SMB, AFP (v3.3), NFS(v3), FTP, FTPS, SFTP, TFTP, HTTP(S), Telnet, | Intel Virtualization Technology (VT- | 1 |
| | SSH, iSCSI, SNMP, SMTP, SMSC | x) | • |
| Dynamic DNS (DDNS) | ✓ | Intel Virtualization Technology for Directed I/O (VT-d) | 1 |
| Ports & interfaces | | Intel VT-x with Extended Page | |
| USB port * | 1 | Tables (EPT) | 4 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | | Intel® AES New Instructions (Intel® | J |
| ports quantity | 4 | AES-NI) | 4 |
| HDMI ports quantity | 1 | Intel® Anti-Theft Technology | × |
| HDMI version | 1.4b | (Intel® AT) | |
| Ethernet LAN (RJ-45) ports * | 4 | Intel [®] Clear Video HD Technology (Intel [®] CVT HD) | 1 |
| Graphics | | Intel [®] Clear Video Technology for | |
| On-board graphics card base | | Mobile Internet Devices (Intel CVT | 1 |
| frequency | 250 MHz | for MID) | |
| On-board graphics card burst | 750 MHz | Intel [®] High Definition Audio (Intel [®] HD Audio) | 1 |
| frequency | | Intel® Hyper Threading Technology | |
| On-board graphics card dynamic | 750 MHz | (Intel® HT Technology) | × |
| frequency (max) | | Intel [®] Identity Protection | 1 |
| Maximum on-board graphics card memory | 8 GB | Technology (Intel® IPT) | - |
| Number of displays supported (on- | 2 | Intel® Insider™ | × |
| board graphics) | 3 | Intel® InTru [™] 3D Technology | × |
| Design | | Intel® OS Guard | × |
| Chassis type * | Rack (1U) | Intel® Quick Sync Video Technology | |
| Cooling type * | Active | Intel® Secure Key | 4 |
| Product colour | Aluminium, Black | Intel® Small Business Advantage (Intel® SBA) | × |
| Number of fans | 2 fan(s) | Intel® Smart Response Technology | × |
| Fan diameter | 4 cm | Intel® Turbo Boost Technology | × |
| LED indicators | HDD, LAN, Status, USB | Intel® Wireless Display (Intel® | |
| | | WiDi) | × |
| Performance | | Maximum number of PCI Express | 6 |
| Type * | NAS | lanes | |
| Backup function * | 4 | Number of execution units | 12 |
| Backup features | Cloud, iSCSI LUN | Thermal Monitoring Technologies | 4 |
| Buzzer | 4 | UART | 1 |
| Multilingual support | | Memory channels supported by processor | Dual |
| Number of users | 4096 user(s) | Memory types supported by | DDR3L, LPDDR3-SDRAM, LPDDR4- |
| Noise level | 38.6 dB | processor | SDRAM |
| Management protocols | SNMP | Operational conditions | |
| Web-based management Share folder access right | 4 | Operating temperature (T-T) | 0 - 40 °C |
| management | 1 | Operating relative humidity (H-H) | 0 - 95% |
| Security algorithms | 256-bit AES, FIPS 140-2, HTTPS, SSH | operating relative number (II-II) | 5 5570 |
| | | | |

Performance

| Reset button | 1 | | |
|------------------------------|--|--|--|
| On/off switch | ✓ | | |
| Built-in iTunes server | ✓ | | |
| Built-in FTP server | ✓ | | |
| Browser supported | Microsoft Internet Explorer 10+, Google Chrome, Mozilla Firefox, Apple Safari 7+ | | |
| System log | ✓ | | |
| Hot spare | ✓ | | |
| S.M.A.R.T. support | ✓ | | |
| Share folder | 512 | | |
| Software | | | |
| Operating system installed * | QNAP Turbo System | | |
| Operating system version | 4.3 | | |
| | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, | | |

Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium,

Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64

Windows operating systems supported

Other features

Processor ARK ID

95594

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.