QNAP TS-673 NAS Tower AMD Embedded R-Series SoC RX-421ND 4 GB DDR4 60 TB HDD QNAP Turbo System Black

Brand : QNAP

Product code: TS-673-4G-60TB-GLD

Product name : TS-673

- Two PCIe Gen3 x4 slots support QM2 cards, 10GbE adapters, or wireless network cards

- Supports the NVIDIA® GeForce® GT1030 graphics card, allowing for 4K video transcoding and output - Dual M.2 SATA 6 Gb/s SSD slots allow for setting up caching or storage pools, improving file access efficiency

- Qtier™ auto-tiering technology and SSD caching enable 24/7 optimized storage efficiency
 - Scalable storage supporting virtualization, containerized apps, centralized storage, backup, sharing, and disaster recovery

- Snapshots fully record system status and data. If files are accidentally deleted or modified, you can quickly restore the data from a snapshot

AMD R RX-421ND (4 x 2.1GHz), 4 GB DDR4, 512 MB DOM, 2 x PCle3.0 x4, 6 x SATA3 2.5"/3.5", 4 x USB 3.0, 4 x RJ-45





Cdlna

Storage		Design	
Supported storage drive interfaces	Serial ATA, Serial ATA II, Serial ATA III	Cable lock slot Cable lock slot type	✓ Kensington
Storage drive sizes supported	2.5,3.5"	Performance	
RAID support *	4	Type *	NAS
RAID levels	0, 1, 5, 6, 10, JBOD	Device class *	Home & Home Office
Hot-swap drive bays	v	Backup function *	
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Backup features	Cloud, USB drive, iSCSI LUN
Storage drives installed *	1	Multilingual support	✓
Total installed storage capacity $*$	60 TB	Noise level	23 dB
Number of storage drives supported	6	Web-based management	✓
* Installed storage drive type *	HDD	Share folder access right management	1
Supported storage drive types *	HDD & SSD	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMP, SSH, SSL/TLS
Processor		Access Control List (ACL)	✓
Processor family *	AMD Embedded R-Series SoC	Reset button	✓
Processor model *	RX-421ND	On/off switch	✓
Processor frequency *	2.1 GHz	Built-in iTunes server	✓
Processor boost frequency	3.4 GHz	Built-in FTP server	✓
Processor cores Memory	4	Browser supported	Internet Explorer 10, Firefox 8, Safari 4, Google Chrome
-	4.00	System log	✓
Internal memory *	4 GB	Hot spare	✓
Internal memory type	DDR4	Password authentication	✓
Maximum RAM supported	64 GB 4	S.M.A.R.T. support	✓
Memory slots	4 SO-DIMM	Share folder	CIFS/SMB
Memory form factor Flash memory	512 MB	Universal Plug and Play (UPnP)	✓
Network	512 115	Software	
Ethernet LAN *	1	Operating system installed *	QNAP Turbo System
Ethernet LAN data rates	10,100,1000 Mbit/s	Operating system version	4.3.4
Wi-Fi	×	Windows operating systems supported	Windows 10, Windows 7, Windows 8
DHCP client	4	Linux operating systems supported	✓
DHCP server	4		
Jumbo frames support	1		
iSCSI support	1		
Wake-on-LAN ready	4		

Network		Software	
Supported network protocols Dynamic DNS (DDNS)	IFS/SMB, AFP (v3.3), NFS(v3), FTP, FTPS, SFTP, TFTP, HTTP(S), Telnet, SSH, ISCSI, SNMP, SMTP, SMSC	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Ports & interfaces			
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Ethernet LAN (RJ-45) ports * Microphone in	Power Power supply location Slots 2 Power supply unit (PSU) capacit	Power	
Audio in/out PCI Express x4 (Gen 3.x) slots		Power supply unit (PSU) capacity	Built-in 250 W
Design		Number of power supply units AC input voltage	1 100 - 240 V
Chassis type * Tower		AC input frequency	50 - 60 Hz
Cooling type * Product colour	Active Black	Weight & dimensions	
Number of fans Fan diameter Fan diameter 2	3 fan(s) 9 cm 6 cm	Width * Depth * Height *	264.3 mm 279.6 mm 188.2 mm
LED indicators Built-in display	√ √	Packaging content	
		Cables included Quick installation guide Number of screws	AC, LAN (RJ-45) ✓ 20
		Operational conditions	

Operating temperature (T-T)

Digital Living Network Alliance (DLNA) certified

Other features

Operating relative humidity (H-H) 5 - 95%

0 - 40 °C

1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.