QNAP

iSCSI support

QNAP TS-h987XU-RP NAS Rack (1U) Intel Xeon E E-2334 16 GB DDR4 8 TB QuTS hero Black, Silver

Brand : QNAP **Product code:** TS-H987XU-RP-E2334-16G/8TB-EXO

ONRP

Product name : TS-h987XU-RP

Intel Xeon E-2334, 16 GB ECC DDR4, 5GB Flash, 4 x 3.5" + 5 x 2.5" U.2, RJ-45, USB 3.2 Gen 2, 2 x 300W PSU, 8.43 kg

QNAP TS-h987XU-RP. Type: NAS. Chassis type: Rack (1U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2334, Processor frequency: 3.4 GHz. Internal memory: 16 GB, Internal memory type: DDR4. Total installed storage capacity: 8 TB. Operating system installed: QuTS hero



Storage		Performance	
Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID expansion RAID rebuild Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types *	2.5,3.5" 0, 1, 5, 6, 10, 50, 60 FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 8 TB 9 HDD & SSD	Device class * Backup function * Backup features Multilingual support Snapshot Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported System log Hot spare	Large Enterprise Business iSCSI LUN 256-bit AES, FIPS 140-2 Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox
Disk roaming	1	Disk scan	✓
Processor		S.M.A.R.T. support Share folder	✓ Thick, Thin
Processor manufacturer * Processor family *	Intel Intel Xeon E	Software	THICK, THIII
Processor model * Processor frequency * Processor boost frequency Processor cores Processor threads Processor cache CPU configuration (max)	E-2334 3.4 GHz 4.8 GHz 4 8 8 MB	Operating system installed * Operating system version	QuTS hero h5.0.0 Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 IoT Enterprise, Windows 10 x64, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8 Enterprise, Windows 8 Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 Romes Reference windows 8 Pro, Windows 8 Reference
Memory Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor ECC Flash memory Network Ethernet LAN * Ethernet LAN data rates	16 GB DDR4 128 GB 4 UDIMM	Windows operating systems supported	
Ethernet LAN data rate supported (max) DHCP server	10000 Mbit/s ✓		
CCCL			

Network		Software	
Wake-on-LAN ready Supported network protocols Dynamic DNS (DDNS)	✓ IPv4, IPv6 ✓	Linux operating systems supported	Debian 7.0, Red Hat Enterprise Linux WS 7.0, SuSE Linux 12.0, SuSE Linux 12.3, SuSE Linux 15, Ubuntu 14.04, Ubuntu 14.10, Ubuntu 15.04, Ubuntu 15.10, Ubuntu 17.10, Ubuntu 18.04 LTS, Ubuntu 20.04 LTS, Ubuntu 22.04 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Ports & interfaces		Emax operating systems supported	
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Concurrent connections PCI Express x8 (Gen 4.x) slots Design	4 4 10000 1	Mac operating systems supported	
	Do els (111)		
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Rack (1U) Active Black, Silver 4 fan(s) 4 cm	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, Solaris 10, Solaris 10
LED indicators	HDD, LAN, Status	Other operating systems supported	SPARC, Solaris 11, Solaris 11 SPARC
Performance		Power	
Type *	NAS	Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (sleep)	250 W 2 120.58 W 114.6 W
		Weight & dimensions	
		Width * Depth * Height * Weight Package weight	430 mm 479 mm 43.3 mm 8.43 kg 11.1 kg
		Packaging content	
		Cables included Power cables quantity Number of screws	AC, LAN (RJ-45) 2 52
		Processor special features	
		Enhanced Intel SpeedStep Technology	1
		Execute Disable Bit Idle States	y
		Intel 64	· /
		Intel Trusted Execution Technology	✓
		Intel Virtualization Technology (VT-x)	✓
		Intel Virtualization Technology for Directed I/O (VT-d)	1
		Intel VT-x with Extended Page Tables (EPT)	1
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

