



# QNAP TS-463XU NAS Rack (1U) AMD G GX-420MC 4 GB DDR3L 32 TB HDD QNAP Turbo System Black



**Brand :** QNAP

**Product code:** TS-463XU-4G-32TB-GLD

**Product name :** TS-463XU

- Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing
  - Qtier™ auto-tiering technology and SSD caching enable constant storage optimization
  - Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks
  - Host containerized applications and virtual machines with various operating systems
  - Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery
  - NAS and iSCSI-SAN (IP-SAN) unified storage solution with scalable design
- AMD GX-420MC 2.0 GHz, 4 GB DDR3L, 512 MB DOM, 4x 2.5/3.5", 2x USB 3.0, 3x USB 2.0, 1x RJ-45 10GBASE-T, 4x RJ-45, 1x PCIe 2.0 x4, 1U + 32TB (WD Gold)

Storage		Design	
Storage drive capacity *	8 TB	Cable lock slot type	Kensington
Storage drive interface *	Serial ATA III	Performance	
Supported storage drive interfaces	Serial ATA III	Type *	NAS
Storage drive size	2.5/3.5"	Device class *	Home & Home Office
Storage drive sizes supported	2.5,3.5"	Backup function *	✓
RAID support *	✓	Backup features	Cloud, iSCSI LUN
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Buzzer	✓
Online RAID migration	✓	Multilingual support	✓
Online RAID expansion	✓	Noise level	36.5 dB
Hot-swap drive bays	✓	Web-based management	✓
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Share folder access right management	✓
Storage drives installed *	✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Total installed storage capacity *	32 TB	Access Control List (ACL)	✓
Number of storage drives installed *	4	Reset button	✓
Number of storage drives supported *	4	On/off switch	✓
Installed storage drive type *	HDD	Built-in iTunes server	✓
Supported storage drive types *	HDD & SSD	Built-in FTP server	✓
Processor		Browser supported	Safari 7+, Chrome, Internet Explorer 10+, Firefox
Processor family *	AMD G	System log	✓
Processor model *	GX-420MC	Hot spare	✓
Processor frequency *	2 GHz	S.M.A.R.T. support	✓
Processor cores	4	Share folder	CIFS/SMB
Memory		Backup button	✓
Internal memory *	4 GB	Software	
Internal memory type	DDR3L	Operating system installed *	QNAP Turbo System
Maximum RAM supported	16 GB	Operating system version	4.3.4
Memory slots	2	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Memory form factor	SO-DIMM	Linux operating systems supported	✓
Flash memory	512 MB	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Network			
Ethernet LAN *	✓		
Ethernet LAN data rates	10,100,1000,10000 Mbit/s		
Ethernet LAN data rate supported (max)	10000 Mbit/s		
Copper ethernet cabling technology	10GBASE-T, 1000BASE-T		

Network		Software	
Wi-Fi	✘	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
DHCP server	✔		
Jumbo frames support	✔		
iSCSI support	✔		
Wake-on-LAN ready	✔		
Supported network protocols	PPTP, L2TP/IPSec, OpenVPN VPN		
Ports & interfaces		Power	
USB port *	✔	Power supply location	Built-in
USB 2.0 ports quantity	3	Power supply unit (PSU) capacity	250 W
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Number of power supply units	1
Ethernet LAN (RJ-45) ports *	5	Power consumption (typical)	50.46 W
Design		Power consumption (HDD standby)	34.06 W
Chassis type *	Rack (1U)	AC input voltage	100 - 240 V
Cooling type *	Active	AC input frequency	50 - 60 Hz
Product colour	Black	Fan voltage	12 V
Number of fans	2 fan(s)	Weight & dimensions	
Fan diameter	4 cm	Width *	439 mm
LED indicators	✔	Depth *	499 mm
Cable lock slot	✔	Height *	44 mm
		Weight	7.58 kg
		Package weight	9.54 kg
		Packaging content	
		Cables included	AC, LAN (RJ-45)
		Quick installation guide	✔
		Sustainability	
		Sustainability certificates	RoHS
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Other features	
		Compliance certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-AUG-2024. Prints or copies of Information are only valid on the printed Publication date