QNAP

QNAP TS-432PXU-2G NAS Rack (1U) Annapurna Labs Alpine AL-324 2 GB DDR4 40 TB HDD Black

Brand: QNAP Product code: TS-432PXU-2G/40TB-GOLD

Product name: TS-432PXU-2G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of $Google^{\scriptscriptstyle\mathsf{TM}}\ G$ Suite and Microsoft $365\, @$
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-432PXU by installing a compatible PCle card
- Increase the storage capacity of the TS-432PXU with QNAP TR RAID expansion enclosures or TL JBOD 4x 3.5", 2GB DDR3, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 250W PSU, 44x439x499 mm



Rack (1U) Active Black 2 fan(s) 4 cm HDD, LAN, Status
NAS Small & Medium Business Cloud, iSCSI LUN 256-bit AES, FIPS 140-2, HTTPS,
SSH, SSL/TLS
✓ ✓ ✓ Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+,
Google Chrome
4.4.3 Windows 10, Windows 7, Windows 8 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X
✓ 4.4.3 Windows 10 ✓ Mac OS X 10 10.11 El Cap Sierra, Mac

Network		Software	
Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system WLAN adapter supported	PPTP, L2TP/IPSec, OpenVPN, QBelt	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity 2	✓	Power supply location Power supply unit (PSU) capacity Number of power supply units	Built-in 250 W 1
	2 SFP+	AC input voltage	100 - 240 V 12 V
		Fan voltage	12 V
		Weight & dimensions	
		Width * Depth * Height * Weight	439 mm 499 mm 44 mm 6.53 kg
		Packaging content	
		Cables included Number of screws	AC, LAN (RJ-45) 28
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

