



# QNAP TS-H886 NAS Tower Ethernet LAN Black, Grey D-1622



Brand : QNAP

Product code: TS-H886-D1622-16G/72TB-GOLD

Product name : TS-H886

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission
  - DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications
  - Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance
  - Two PCIe slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
  - Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery
  - QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business
- Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2, 231.9x292.9x319.8 mm

| Storage  |                                    | Performance                         |   |
|--|------------------------------------|-------------------------------------|---|
| Supported storage drive interfaces             | Serial ATA II, Serial ATA III      | Buzzer                              | ✓   |
| Storage drive sizes supported                  | 2.5,3.5"                           | Multilingual support                | ✓   |
| Number of M.2 (M & B) slots                    | 2                                  | Noise level                         | 20.4 dB   |
| RAID support *                                 | ✓                                  | Snapshot                            | ✓   |
| RAID levels                                    | 0, 1, 5, 6, 10, 50, 60             | Web-based management                | ✓   |
| Online RAID migration                          | ✓                                  | Security algorithms                 | 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS   |
| Online RAID expansion                          | ✓                                  | Access Control List (ACL)           | ✓   |
| RAID rebuild                                   | ✓                                  | Reset button                        | ✓   |
| Hot-swap drive bays                            | ✓                                  | On/off switch                       | ✓   |
| Supported file systems                         | FAT32, HFS+, NTFS, ZFS, ext3, ext4 | Built-in FTP server                 | ✓   |
| Storage drives installed *                     | ✓                                  | Browser supported                   | Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox  |
| Total installed storage capacity *             | 72 TB                              | System log                          | ✓   |
| Number of storage drives installed *           | 8                                  | Hot spare                           | ✓   |
| Number of storage drives supported *           | 8                                  | S.M.A.R.T. support                  | ✓   |
| Installed storage drive type *                 | HDD                                | Share folder                        | CIFS/SMB  |
| Supported storage drive types *                | HDD & SSD                          | Universal Plug and Play (UPnP)      | ✓   |
| Bad block scan                                 | ✓                                  | USB copy function                   | ✓   |
| Disk roaming                                   | ✓                                  |                                     |   |
| Processor                                      |                                    | Software                            |   |
| Processor manufacturer *                       | Intel                              | Operating system installed *        | QNAP Turbo System   |
| Processor family *                             | Intel® Xeon® D                     | Operating system version            | 4.5.0   |
| Processor model *                              | D-1622                             | Windows operating systems supported | Windows 10, Windows 7, Windows 8  |
| Processor frequency *                          | 2.6 GHz                            | Linux operating systems supported   | ✓   |
| Processor boost frequency                      | 3.2 GHz                            | Mac operating systems supported     | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina |
| Processor cores                                | 4                                  | Server operating systems supported  | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019   |
| Processor threads                              | 8                                  |                                     |   |
| Processor cache                                | 6 MB                               | Power                               |   |
| CPU configuration (max)                        | 1                                  | Power supply location               | Built-in  |
| PCI Express slots version                      | 2.0, 3.0                           | Power supply unit (PSU) capacity    | 250 W   |
| Processor lithography                          | 14 nm                              | Number of power supply units        | 1   |
| Processor operating modes                      | 64-bit                             | Power consumption (typical)         | 75.79 W   |
| Processor package size                         | 37.5 x 37.5 mm                     | AC input voltage                    | 100 - 240 V   |
| Scalability                                    | 1S                                 | AC input frequency                  | 50 - 60 Hz  |
| Tcase  | 83 °C                              |                                     |   |
| Tjunction                                      | 105 °C                             |                                     |   |
| Thermal Design Power (TDP)                     | 40 W                               |                                     |   |
| On-board graphics card model                   | Not available                      |                                     |   |
| Maximum internal memory supported by processor | 128 GB                             |                                     |   |

|   |                           |  |                        |
|---|---------------------------|--|------------------------|
| <b>Memory</b>                                   |                           | <b>Weight &amp; dimensions</b>                           |                        |
| Internal memory type                            | DDR4                      | Width *  | 292.9 mm               |
| Maximum RAM supported                           | 128 GB                    | Depth *  | 319.8 mm               |
| Internal memory *                               | 16 GB                     | Height *   | 231.9 mm               |
| Memory form factor                              | UDIMM                     | Weight   | 8.5 kg                 |
| Flash memory                                    | 5000 MB                   | <b>Packaging content</b>                                 |                        |
| <b>Network</b>                                  |                           | Cables included  | AC, LAN (RJ-45)        |
| Ethernet LAN *                                  | ✓                         | Number of screws   | 32                     |
| Ethernet LAN data rates                         | 10,100,1000,2500 Mbit/s   | <b>Processor special features</b>                        |                        |
| DHCP client                                     | ✓                         | Embedded options available                               | ✗                      |
| DHCP server                                     | ✓                         | Enhanced Intel SpeedStep Technology                      | ✓                      |
| Jumbo frames support                            | ✓                         | Execute Disable Bit                                      | ✓                      |
| Supported network protocols                     | TCP/IP, HTTP/HTTPS        | Idle States  | ✓                      |
| <b>Ports &amp; interfaces</b>                   |                           | Intel 64   | ✓                      |
| USB port *                                      | ✓                         | Intel QuickAssist Technology                             | ✗                      |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 3                         | Intel Trusted Execution Technology                       | ✓                      |
| Ethernet LAN (RJ-45) ports *                    | 4                         | Intel TSX-NI   | ✓                      |
| PCI Express x8 (Gen 3.x) slots                  | 2                         | Intel Virtualization Technology (VT-x)                   | ✓                      |
| <b>Design</b>                                   |                           | Intel Virtualization Technology for Directed I/O (VT-d)  | ✓                      |
| Chassis type *                                  | Tower                     | Intel VT-x with Extended Page Tables (EPT)               | ✓                      |
| Cooling type *                                  | Active                    | Intel® AES New Instructions (Intel® AES-NI)              | ✓                      |
| Product colour                                  | Black, Grey               | Intel® Hyper Threading Technology (Intel® HT Technology) | ✓                      |
| Number of fans                                  | 3 fan(s)                  | Intel® OS Guard  | ✓                      |
| Fan diameter                                    | 8 cm                      | Intel® Secure Key  | ✓                      |
| Fan diameter 2                                  | 9.7 cm                    | Intel® Turbo Boost Technology                            | 2.0                    |
| LED indicators                                  | HDD, SSD, Status          | Maximum number of PCI Express lanes                      | 32                     |
| Built-in display                                | ✓                         | Thermal Monitoring Technologies                          | ✓                      |
| Cable lock slot                                 | ✓                         | Memory types supported by processor                      | DDR3-SDRAM, DDR4-SDRAM |
| Cable lock slot type                            | Kensington                | <b>Operational conditions</b>                            |                        |
| <b>Performance</b>                              |                           | Operating temperature (T-T)                              | 0 - 35 °C              |
| Type *  | NAS                       | Operating relative humidity (H-H)                        | 5 - 95%                |
| Device class *                                  | Large Enterprise Business | <b>Other features</b>                                    |                        |
| Backup function *                               | ✓                         | Processor ARK ID   | 193687                 |
| Backup features                                 | Cloud, iSCSI LUN          |  |                        |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date