



## LevelOne 8-Port PS/2-USB VGA KVM Switch

Brand : LevelOne

Product code: KVM-0831

Product name : 8-Port PS/2-USB VGA KVM Switch

8-Port Combo KVM Switch, USB, VGA, 1920 x 1440px, 8 LEDs, 5~99 sec, 1U

LevelOne 8-Port PS/2-USB VGA KVM Switch. Keyboard port type: USB, Mouse port type: USB, Video port type: VGA. Maximum resolution: 1920 x 1440 pixels, Scan interval: 5,99 s, Maximum operating distance: 300 m. Product colour: Black, Grey, Rack capacity: 1U, Mean time between failures (MTBF): 75138.181 h. Output voltage: 12 V, Output current: 1 A. Other operating systems supported: Novell NetWare 3.x, Novell NetWare 4.x, Novell NetWare 6.x



Ports & interfaces		Power	
Number of computers controlled *	8	Output current	1 A
Keyboard port type *	USB	<b>System requirements</b>	
Mouse port type *	USB	Windows operating systems supported	✓
Video port type *	VGA	Linux operating systems supported	✓
VGA (D-Sub) ports quantity	8	Mac operating systems supported	✓
Console ports *	USB A, VGA (D-Sub)	Other operating systems supported	Novell NetWare 3.x, Novell NetWare 4.x, Novell NetWare 6.x
Console USB ports quantity	2	<b>Operational conditions</b>	
USB connector type	USB Type-A	Operating temperature (T-T)	0 - 50 °C
Audio connections	✗	Storage temperature (T-T)	-20 - 60 °C
DC-in jack	✓	Operating relative humidity (H-H)	0 - 95%
<b>Performance</b>		<b>Weight &amp; dimensions</b>	
Maximum resolution *	1920 x 1440 pixels	Width	160 mm
Scan interval	5,99 s	Depth	445 mm
Hot-Plug support	✓	Height	45 mm
Maximum operating distance	300 m	<b>Packaging data</b>	
<b>Design</b>		Package width	325 mm
Rack mounting *	✓	Package depth	550 mm
Rack capacity	1U	Package height	320 mm
Product colour *	Black, Grey	Package weight	9.6 kg
Cascadable	✓	<b>Packaging content</b>	
LED indicators	✓	Manual	✓
Push button	✓	AC adapter included	✓
Hot keys	✓	Rack mount kit	✓
Mean time between failures (MTBF)	75138.181 h	Rubber feet	✓
<b>Display</b>		<b>Logistics data</b>	
Built-in display *	✓	Harmonized System (HS) code	85176200
On Screen Display (OSD)	✓	Country of origin	China
<b>Power</b>			
Output voltage	12 V		



4015867138076

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date