## QNAP

## QNAP TS-432PXU-2G NAS Rack (1U) Annapurna Labs Alpine AL-324 2 GB DDR4 48 TB HDD Black

**Brand**: QNAP Product code: TS-432PXU-2G/48TB-GOLD

Product name: TS-432PXU-2G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google™ G Suite and Microsoft 365®
  - Snapshots fully record system status and data, allowing you to protect files and data from accidental
- deletion and malware attacks
- Expand the application potential of the TS-432PXU by installing a compatible PCle card
- Increase the storage capacity of the TS-432PXU with QNAP TR RAID expansion enclosures or TL JBOD 4x 3.5", 2GB DDR3, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 250W PSU, 44x439x499 mm



Storage		Design	
Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types *		Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators	Rack (1U) Active Black 2 fan(s) 4 cm HDD, LAN, Status
		Performance  Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Web-based management	NAS Small & Medium Business  Cloud, iSCSI LUN    256-bit AES, FIPS 140-2, HTTPS,
Processor	•	Security algorithms Access Control List (ACL)	SSH, SSL/TLS ✓
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor cores	Annapurna Labs Annapurna Labs Alpine AL-324 1.7 GHz	Reset button On/off switch Built-in FTP server Browser supported	✓ ✓ Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+,
Memory		System log	Google Chrome
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory	2 GB DDR4 16 GB 1 UDIMM 512 MB	Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) USB copy function	✓ ✓ CIFS/SMB ✓
Network	312 MD	Software	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) DHCP client DHCP server Jumbo frames support iSCSI support	100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system version Windows operating systems supported Linux operating systems supported  Mac operating systems supported	4.4.3 Windows 10, Windows 7, Windows 8  ✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina

Network		Software	
Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system WLAN adapter supported	PPTP, L2TP/IPSec, OpenVPN, QBelt	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
Ports & interfaces  USB port *  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity  Fiber ports quantity  Fiber optic connector  Ethernet LAN (RJ-45) ports *  2	<b>✓</b>		Built-in 250 W 1
	2 SFP+	AC input voltage	100 - 240 V 12 V
		Fan voltage	12 V
		Weight & dimensions	
		Width * Depth * Height * Weight	439 mm 499 mm 44 mm 6.53 kg
		Packaging content	
		Cables included Number of screws	AC, LAN (RJ-45) 28
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

