## QNAP

## QNAP TS-H3087XU-RP NAS Rack (4U) Intel Xeon E E-2378 64 GB DDR4 432 TB QuTS hero Black, White

**Brand**: QNAP Product code: TS-H3087XU-RP-E2378-64G/432TB-

Product name: TS-H3087XU-RP

Intel Xeon E-2378, 64 GB ECC DDR4, 5GB Flash, 24 x 3.5" SATA + 6 x 2.5" SATA, RJ-45, USB 3.2 Gen 2, 4U, 21.78 kg

QNAP TS-H3087XU-RP. Type: NAS. Chassis type: Rack (4U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2378, Processor frequency: 2.6 GHz. Internal memory: 64 GB, Internal memory type: DDR4. Total installed storage capacity: 432 TB. Operating system installed: QuTS hero



Performance	
Backup function *	<b>/</b>
·	Cloud, iSCSI LUN
- ''	15000 ( )
	16000 user(s)
•	✓
- ·	SMB/CIFS, AFP, NFS
•	✓
3	✓
Security algorithms	HTTPS, SNMPv2, SNMPv3, SSH
Access Control List (ACL)	✓
Reset button	✓
On/off switch	✓
Built-in FTP server	✓
Browser supported	Apple Safari (latest version), Google Chrome (latest version), Microsoft Edge (latest version), Mozilla Firefox (latest version)
System log	✓
Hot spare	✓
Disk scan	✓
S.M.A.R.T. support	✓
Share folder	Thick, Thin
Software	
Operating system installed *	QuTS hero
	h5.0.0
3 3,5 5	
	Access Control List (ACL) Reset button On/off switch Built-in FTP server  Browser supported  System log Hot spare Disk scan S.M.A.R.T. support Share folder

Matanada		Coffee	
Network Conner othernet cabling technology	10CDACE T	Software	Windows 10 Windows 10
Copper ethernet cabling technology DHCP server iSCSI support Supported network protocols Dynamic DNS (DDNS)	10GBASE-T  ✓  ✓  IPv4, IPv6  ✓		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise
Ports & interfaces			Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Number of SATA III connectors PCI Express x8 (Gen 4.x) slots	4 4 30 1	Windows operating systems supported	x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7
Design			Professional x64, Windows 7 Starter, Windows 7 Starter x64
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Rack (4U) Active Black, White 4 fan(s) 8 cm		Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 CentOS 7.0, Ubuntu 14.04,
LED indicators	HDD, LAN, Status, USB	Linux operating systems supported	openSUSE 12.1, openSUSE 12.2
Performance Type * NAS	S rge Enterprise Business	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
		Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Other operating systems supported	IBM AIX 7.1, Solaris 10
		Power	
		Power supply location Power supply unit (PSU) capacity	Built-in 800 W 2
		Power supply location Power supply unit (PSU) capacity Number of power supply units	
		Power supply location Power supply unit (PSU) capacity	800 W
		Power supply location Power supply unit (PSU) capacity Number of power supply units  Weight & dimensions  Width * Depth * Height * Weight	800 W 2 483 mm 630 mm 178 mm 21.8 kg
		Power supply location Power supply unit (PSU) capacity Number of power supply units  Weight & dimensions  Width * Depth * Height * Weight Package weight	800 W 2 483 mm 630 mm 178 mm 21.8 kg
		Power supply location Power supply unit (PSU) capacity Number of power supply units  Weight & dimensions  Width * Depth * Height * Weight Package weight  Packaging content  Cables included Power cables quantity Number of screws	800 W 2 483 mm 630 mm 178 mm 21.8 kg 29.6 kg AC, LAN (RJ-45)
		Power supply location Power supply unit (PSU) capacity Number of power supply units  Weight & dimensions  Width * Depth * Height * Weight Package weight  Packaging content  Cables included Power cables quantity	800 W 2 483 mm 630 mm 178 mm 21.8 kg 29.6 kg AC, LAN (RJ-45)

Operating temperature (T-T)

0 - 40 °C

## Operational conditions

Operating relative humidity (H-H) \$5 - 95% Storage temperature (T-T) \$-20 -  $70\ ^{\circ}\text{C}$ 

