## QNAP TS-1263XU NAS Rack (2U) AMD G GX-420MC 4 GB DDR3L 72 TB HDD QNAP Turbo System Black

Brand : QNAP

Product code: TS-1263XU-4G-72TB-GLD

Product name : TS-1263XU

- Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing

- Qtier  $\ensuremath{^{\rm M}}$  auto-tiering technology and SSD caching enable constant storage optimization

- Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks

- Host containerized applications and virtual machines with various operating systems

- Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery - RAID 50/60 is recommended for NAS with over 10 disks to strike a balance between capacity, protection, and performance

AMD GX-420MC 2.0 GHz, 4 GB DDR3L, 512 MB DOM, 12x 2.5/3.5", 2x USB 3.0, 2x USB 2.0, 1x RJ-45 10GBASE-T, 4x RJ-45, 1X PCIe 2.0 x4, 2U + 72TB (WD Gold)







Storage		Design	
Storage drive capacity *	6 ТВ	Cable lock slot type	Kensington
Storage drive interface *	Serial ATA III	Performance	
Supported storage drive interfaces		Туре *	NAS
Storage drive size	2.5/3.5"	Device class *	Home & Home Office
Storage drive sizes supported	2.5,3.5"	Backup function *	1
RAID support *		Backup features	Cloud, iSCSI LUN
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Buzzer	4
Online RAID migration		Multilingual support	4
Online RAID expansion	1	Noise level	35.7 dB
Hot-swap drive bays	V	Web-based management	4
Supported file systems Storage drives installed *	FAT32, HFS+, NTFS, ext3, ext4 ✓	Share folder access right management	✓
Total installed storage capacity * Number of storage drives installed *	72 TB 12	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Number of storage drives supported	12	Access Control List (ACL)	4
*		Reset button	4
Installed storage drive type *	HDD	On/off switch	1
Supported storage drive types *	HDD & SSD	Built-in iTunes server	1
Bad block scan	4	Built-in FTP server	4
Processor	AMD G	Browser supported	Safari 7+, Chrome, Internet Explorer 10+, Firefox
Processor family *	GX-420MC	System log	4
Processor model * Processor frequency *	2 GHz	Hot spare	4
Processor cores	4	S.M.A.R.T. support	1
FIOLESSOI COTES	4	Share folder	CIFS/SMB
Memory		Universal Plug and Play (UPnP)	1
Internal memory *	4 GB	Software	
Internal memory type	DDR3L	Operating system installed *	QNAP Turbo System
Maximum RAM supported	16 GB	Operating system version	4.3.4
Memory slots Memory form factor	2 SO-DIMM	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Flash memory	512 MB	Linux operating systems supported	1
Network			Mac OS X 10.10 Yosemite, Mac OS X
Ethernet LAN *	1		10.11 El Capitan, Mac OS X 10.12
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8
Ethernet LAN data rate supported (max)	10000 Mbit/s		Mountain Lion, Mac OS X 10.9 Mavericks
(			

Network		Software	
Copper ethernet cabling technology Wi-Fi DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols	10GBASE-T, 1000BASE-T X V V PPTP, L2TP/IPSec, OpenVPN VPN	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
		Power	
		Power supply location Power supply unit (PSU) capacity	Built-in 350 W
Ports & interfaces		Number of power supply units Power consumption (HDD standby)	1 44.78 W
USB port * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	<ul><li>✓</li><li>2</li><li>2</li></ul>	AC input voltage AC input frequency Fan voltage	100 - 240 V 50 - 60 Hz 12 V
Ethernet LAN (RJ-45) ports *	5	Weight & dimensions	
Design		Width *	482 mm
Chassis type *RateCooling type *ActProduct colourBl	Rack (2U) Active Black 2 fan (a)	Depth * Height * Weight Package weight	534 mm 89 mm 11.8 kg 13.9 kg
Fan diameter	2 fan(s) 7 cm	Packaging content	
LED indicators Cable lock slot	HDD, LAN, USB ✓	Cables included Quick installation guide	AC, LAN (RJ-45) ✔
		Sustainability	
		Sustainability certificates	RoHS
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%
		Other features	

Compliance certificates

RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.