

NETGEAR WBE750 11530 Mbit/s White Power over Ethernet (PoE)

Brand : NETGEAR

Product code: WBE750-100EUS

Product name : WBE750



- Tri-Band access point delivering 18.4Gbps of data throughput
- 10G/Multi-Gig Ethernet port ensures full bandwidth connection for maximum speed
- Up to 8 separate wireless networks (SSIDs)
- WPA3 encryption for the highest level of WiFi connection security
- Cloud management without the need for a controller
- Small form factor for a more incognito appearance
- Simplified deployment with PoE++ for single cable power & data
- Backwards compatible with older WiFi devices for a future-proofed solution

Tri-Band PoE 10G Insight Manageable WiFi 7 Access Point

NETGEAR WBE750. Maximum data transfer rate: 11530 Mbit/s, Maximum data transfer rate (2.4 GHz): 1147 Mbit/s, Maximum data transfer rate (5 GHz): 5765 Mbit/s. Security algorithms: 802.1x RADIUS, SSL/TLS, WPA, WPA2, WPA3. Service Set Identifier (SSID) features: SSID broadcast. DC voltage range: 12 V, Input current: 3.5 A. Placement: Ceiling, Wall, Product colour: White. Antenna type: Internal

Features		Management features	
2.4 GHz *	✓	Web-based management	✓
5 GHz *	✓	Ports & interfaces	
6 GHz *	✓	Ethernet LAN (RJ-45) ports *	1
Maximum data transfer rate *	11530 Mbit/s	DC-in jack	✓
Maximum data transfer rate (2.4 GHz)	1147 Mbit/s	Power	
Maximum data transfer rate (5 GHz)	5765 Mbit/s	Power over Ethernet (PoE) *	✓
Maximum data transfer rate (6 GHz)	11530 Mbit/s	DC voltage range	12 V
Ethernet LAN data rates	10000 Mbit/s	Input current	3.5 A
Throughput data rate	18400 Mbit/s	Design	
	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n	Placement *	Ceiling, Wall
Networking standards		Product colour *	White
MIMO	✓	LED indicators	✓
MIMO type	Multi User MIMO	Antenna	
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna type *	Internal
VLAN support	✓	Weight & dimensions	
Security		Width	266.6 mm
Security algorithms *	802.1x RADIUS, SSL/TLS, WPA, WPA2, WPA3	Depth	268.3 mm
MAC address filtering	✓	Height	55.5 mm
Service Set Identifier (SSID) features	SSID broadcast	Weight	2.31 kg
Auto Wireless Distribution System (WDS)	✓	Packaging content	
Access Control List (ACL)	✓	Number of products included	1 pc(s)
		Mounting kit	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C



0606449167726



606449167726

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.