QNAP

QNAP TS-863XU NAS Rack (2U) AMD G GX-420MC 4 GB DDR3L 48 **TB HDD QNAP Turbo System Black**

Brand: QNAP Product code: TS-863XU-4G-48TB-GLD

Product name: TS-863XU

Supported network protocols

- Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks
- Host containerized applications and virtual machines with various operating systems
- Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery
- NAS and iSCSI-SAN (IP-SAN) unified storage solution with scalable design

AMD G-Series GX-420MC 2.0 GHz, 4 GB DDR3L, 512MB DOM, 8x 2.5"/3.5" SATA III, 2x USB 3.0, 2x USB

2.0, 1x PCle 2.0 x4, 1x RJ-45 10GBASE-T, 4x 1G RJ-45, 2U, 89x482x534 mm



| Storage | | Design | |
|--|---|--|---|
| Supported storage drive interfaces Storage drive sizes supported RAID support * | Serial ATA III 2.5,3.5" ✓ | LED indicators Cable lock slot Cable lock slot type | HDD, LAN, USB ✓ Kensington |
| RAID levels | 0, 1, 5, 6, 10, 50, 60, JBOD | Performance | |
| Online RAID migration Online RAID expansion Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types * | ✓ ✓ FAT32, HFS+, NTFS, ext3, ext4 ✓ 48 TB 8 HDD HDD & SSD | Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Web-based management Share folder access right | NAS Small & Medium Business Cloud, iSCSI LUN 35 dB |
| Bad block scan Processor | ✓ | management Security algorithms | 256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS |
| Processor family * Processor model * Processor frequency * Processor cores Memory Internal memory * | AMD G GX-420MC 2 GHz 4 | Access Control List (ACL) Reset button On/off switch Built-in iTunes server Built-in FTP server Browser supported | Safari 7+, Chrome, Internet Explorer 10+, Firefox |
| Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory | DDR3L 16 GB 2 SO-DIMM 512 MB | System log Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) | ✓ ✓ ✓ CIFS/SMB |
| Network | | Software | |
| Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) | 10,100,1000,10000 Mbit/s 10000 Mbit/s | Operating system installed * Operating system version Windows operating systems supported | QNAP Turbo System 4.3.4 Windows 10, Windows 7, Windows 8 |
| Copper ethernet cabling technology Wi-Fi DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready | 10GBASE-T, 1000BASE-T X ✓ | Linux operating systems supported Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |

PPTP, L2TP/IPSec, OpenVPN VPN

| Ports & interfaces | | Software | |
|---|--------------------------------------|--|--|
| USB port * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | √ 2 2 | Server operating systems supported | Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016 |
| Ethernet LAN (RJ-45) ports * | 5 | Power | |
| Chassis type * Cooling type * Product colour Number of fans Fan diameter | Rack (2U) Active Black 2 fan(s) 7 cm | Power supply location Power supply unit (PSU) capacity Number of power supply units AC input voltage Fan voltage Weight & dimensions Width * | Built-in 250 W 1 100 - 240 V 12 V |
| | | Depth * Height * | 534 mm 89 mm |
| | | Packaging content | |
| | | Cables included Quick installation guide | AC, LAN (RJ-45) ✓ |
| | | Operational conditions | |
| | | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C 5 - 95% |

