NETGEAR M4300-8X8F Managed L3 10G Ethernet (100/1000/10000) 1U Black

Brand: NETGEAR **Product code**: XSM4316S-100NES

320 Gbps, 10/100/1000/10000, 1U, L3

Product name: M4300-8X8F

NETGEAR M4300-8X8F. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8, USB 2.0 ports quantity: 1, Console port: RJ-45/Mini-USB. MAC address table: 16000 entries, Switching capacity: 320 Gbit/s. Networking standards: IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az. Rack mounting, Form factor: 1U



Management features		Multicast features	
Switch type *	Managed	Number of multicast groups filtered	4000
Switch layer	L3	Design	
Quality of Service (QoS) support	✓	Rack mounting *	√
Web-based management	✓	Stackable *	·
ARP inspection	✓	Form factor	10
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports quantity *	8	LED indicators	Activity, Power, Speed
Basic switching RJ-45 Ethernet ports	10G Ethernet (100/1000/10000)	Safety	CSA 22.2 #950, UL 1950)/cUL IEC 950/EN 60950
type * SFP+ module slots quantity	8	Electromagnetic compatibility	CE, FCC 15 A, VCCI A, A EN 55022, (CISPR 22) A, EN 50082-1, EN 55024
Fiber optic connector	SFP+	Performance	
Console port	RJ-45/Mini-USB		,
USB 2.0 ports quantity	1	Built-in processor	000 MH=
Network		Processor frequency	800 MHz
nether k	IEEE 802.11ad, IEEE 802.11az, IEEE	Internal memory	1024 MB 256 MB
Networking standards *	802.3ad, IEEE 802.3az	Flash memory Noise level	36.9 dB
10G support *	1	Mean time between failures (MTBF)	
Cable types supported	Cat5, Cat5e, Cat6, Cat7		130120 11
Port mirroring	✓	Power	
IP routing	✓	Power supply included *	✓
Flow control support	✓	Number of power supply units	1
Link aggregation	✓	AC input voltage	120 - 230 V
Rate limiting	✓	Power consumption (max)	49 W
Auto MDI/MDI-X	✓	Power over Ethernet (PoE)	
Spanning tree protocol	✓	Power over Ethernet (PoE) *	×
Auto-sensing	✓	Operational conditions	
Auto-negotiation	V	Operating temperature (T-T)	0 - 50 °C
VLAN support	√	Storage temperature (T-T)	-20 - 70 °C
Virtual LAN features	Private VLAN	Operating relative humidity (H-H)	0 - 90%
Optical fiber		Storage relative humidity (H-H)	0 - 95%
Fiber ethernet cabling technology	10GBASE-LR, 10GBASE-LRM, 10GBASE-SR	Operating altitude	0 - 3000 m
Data transmission		Non-operating altitude Heat dissipation	0 - 3000 m 18577 BTU/h
Switching capacity *	320 Gbit/s 357 Mpps 16000 entries ✓	Weight & dimensions	
Forwarding rate		-	212 mm
MAC address table *		Width	212 mm
Store-and-forward		Depth	345 mm
Number of static routes	64	Height	44 mm
		Weight	3.32 kg

Data transmission		Packaging data	
Jumbo frames support Jumbo frames	√ 9000	Cables included User guide	AC, LAN (RJ-45), Mini-USB ✓
Security		Rack mount kit Rubber feet	1
DHCP features DHCP server, DHCP client Access Control List (ACL) ✓	Resource CD	,	
Security algorithms	HTTPS, SNMP, SSH	Logistics data	
SSH/SSL support BPDU filtering/protection	✓	Harmonized System (HS) code	85176990
Multicast features			
Multicast support	√		





606449110005

0606449110005

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.