



QNAP TS-1232XU NAS Rack (2U) Annapurna Labs Alpine AL-324 4 GB DDR4 72 TB HDD QNAP Turbo System Black



Brand : QNAP

Product code: TS-1232XU-4G-72TB-GLD

Product name : TS-1232XU

2U, 12-Bay, Alpine AL-324, Quad-Core, 1.7GHz, 64-bit, 4 GB DDR4, 512MB DOM, 2.5", 3.5", SATA III, RJ-45, SFP+, USB 3.0, PCIe 2.0x2, 11.3kg, 250W PSU, 72TB (WD Gold)
 QNAP TS-1232XU. Type: NAS. Chassis type: Rack (2U). Device class: Large Enterprise Business.
 Processor family: Annapurna Labs, Processor model: Alpine AL-324, Processor frequency: 1.7 GHz.
 Internal memory: 4 GB, Internal memory type: DDR4. Total installed storage capacity: 72 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System

| Storage | | Design | |
|--|--------------------------------------|-------------------------------------|---|
| Storage drive capacity * | 6 TB | Chassis type * | Rack (2U) |
| Storage drive interface * | Serial ATA III | Cooling type * | Active |
| Supported storage drive interfaces | Serial ATA III | Product colour | Black |
| Storage drive size | 2.5/3.5" | Number of fans | 2 fan(s) |
| Storage drive sizes supported | 2.5,3.5" | Fan diameter | 7 cm |
| RAID support * | ✓ | Fan diameter 2 | 7 cm |
| RAID levels | 0, 1, 5, 6, 10, JBOD | LED indicators | HDD, LAN, Status |
| Online RAID migration | ✓ | Cable lock slot | ✓ |
| Online RAID expansion | ✓ | Cable lock slot type | Kensington |
| RAID rebuild | ✓ | Performance | |
| Hot-swap drive bays | ✓ | Type * | NAS |
| Supported file systems | FAT32, HFS+, NTFS, exFAT, ext3, ext4 | Device class * | Large Enterprise Business |
| Storage drives installed * | ✓ | Backup function * | ✓ |
| Total installed storage capacity * | 72 TB | Backup features | Cloud, iSCSI LUN |
| Number of storage drives installed * | 12 | Buzzer | ✓ |
| Number of storage drives supported * | 12 | Noise level | 24.5 dB |
| Installed storage drive type * | HDD | Snapshot | ✓ |
| Supported storage drive types * | HDD & SSD | Security algorithms | 256-bit AES, HTTPS, SSH |
| Bad block scan | ✓ | Reset button | ✓ |
| Processor | | On/off switch | ✓ |
| Processor family * | Annapurna Labs | Browser supported | Apple Safari 7, Google Chrome, Microsoft Internet Explorer 10, Mozilla Firefox |
| Processor model * | Alpine AL-324 | S.M.A.R.T. support | ✓ |
| Processor frequency * | 1.7 GHz | Universal Plug and Play (UPnP) | ✓ |
| Processor cores | 4 | Software | |
| Processor architecture | ARM Cortex-A57 | Operating system installed * | QNAP Turbo System |
| Memory | | Operating system version | 4.3.4 |
| Internal memory * | 4 GB | Windows operating systems supported | Windows 10, Windows 7, Windows 8 |
| Internal memory type | DDR4 | Linux operating systems supported | ✓ |
| Maximum RAM supported | 16 GB | Mac operating systems supported | Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| Memory slots | 1 | Server operating systems supported | Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016 |
| Memory form factor | UDIMM | Power | |
| Flash memory | 512 MB | Power supply location | Built-in |
| Network | | Power supply unit (PSU) capacity | 250 W |
| Ethernet LAN * | ✓ | | |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | | |
| Ethernet LAN data rate supported (max) | 10000 Mbit/s | | |
| Wi-Fi | ✗ | | |

| Network | | Power | |
|---|------|-----------------------------------|-----------------|
| DHCP client | ✓ | Number of power supply units | 1 |
| DHCP server | ✓ | AC input voltage | 100 - 240 V |
| Jumbo frames support | ✓ | AC input frequency | 50 - 60 Hz |
| iSCSI support | ✓ | Fan voltage | 12 V |
| Wake-on-LAN ready | ✓ | Output current | 3.5 A |
| Dynamic DNS (DDNS) | ✓ | Weight & dimensions | |
| Ports & interfaces | | Width * | 482 mm |
| USB port * | ✓ | Depth * | 534 mm |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 | Height * | 89 mm |
| Fiber ports quantity | 2 | Weight | 11.3 kg |
| Fiber optic connector | SFP+ | Packaging content | |
| Ethernet LAN (RJ-45) ports * | 2 | Cables included | AC, LAN (RJ-45) |
| | | Quick installation guide | ✓ |
| | | Number of screws | 84 |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 40 °C |
| | | Operating relative humidity (H-H) | 5 - 95% |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-AUG-2024. Prints or copies of Information are only valid on the printed Publication date