QNAP

QNAP TVS-673e NAS Tower AMD Embedded R-Series SoC RX-421BD 4 GB DDR4 48 TB HDD QNAP Turbo System Black, Bronze

Brand : QNAP Product code: TVS-673E-4G/48TB-EXOS

Product name: TVS-673e

AMD RX-421BD (2.1/3.4GHz), 4GB DDR4 (2133Mhz), Gigabit LAN QNAP TVS-673e. Type: NAS. Chassis type: Tower. Device class: Small & Medium Business. Processor family: AMD Embedded R-Series SoC, Processor model: RX-421BD, Processor frequency: 2.1 GHz. Internal memory: 4 GB, Internal memory type: DDR4. Total installed storage capacity: 48 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System





Chamana		Dogima	
Storage		Design	
Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels Online RAID migration	M.2, Serial ATA III 2.5,3.5,M.2 2 √ 0, 1, 5+S, 5, 6, 6+HS, 10+HS, 10, JBOD √	LED indicators Built-in display Display type Cable lock slot Cable lock slot type Built-in speaker(s) Number of built-in speakers	HDD, LAN, Status, USB LCD Kensington 1
Online RAID expansion	✓	Performance	
Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type *	FAT32, HFS+, exFAT, ext3, ext4 48 TB 6 HDD	Type * Device class * Backup function * Backup features Number of users Noise level	NAS Small & Medium Business ✓ Cloud, USB drive, iSCSI LUN 4096 user(s) 23 dB
Supported storage drive types *	HDD & SSD	Third-party support	✓
Processor		Snapshot	✓
Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores On-board graphics card model	AMD Embedded R-Series SoC RX-421BD 2.1 GHz 3.4 GHz 4 AMD Radeon R7	Management protocols Web-based management Share folder access right management Security algorithms Reset button On/off switch	SNMP
Memory		Built-in iTunes server	✓
Internal memory * Internal memory type Memory clock speed Maximum RAM supported Memory slots Memory form factor Flash memory	4 GB DDR4 2133 MHz 64 GB 4 SO-DIMM 512 MB	Built-in FTP server Browser supported System log Hot spare Share folder Remotely operated	Microsoft Internet Explorer 10+, Google Chrome, Apple Safari 7+, Mozilla Firefox
Network		Backup button	<i>'</i>
Ethernet LAN * Ethernet LAN data rates	10,100,1000 Mbit/s	Universal Plug and Play (UPnP) USB copy function	4
Wi-Fi DHCP client DHCP server Jumbo frames support	× √ √	Software Operating system installed * Operating system version	QNAP Turbo System 4.3

Network		Software	
iSCSI support Wake-on-LAN ready Supported network protocols Link aggregation Dynamic DNS (DDNS) WLAN adapter supported	CIFS/SMB, AFP (v3.3), FTP, FTPS, HTTP(S), Telnet, SSH, iSCSI, SNMP, SMTP	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64
Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity HDMI ports quantity HDMI version Ethernet LAN (RJ-45) ports * 3.5 mm (1/8-inch) out PCI Express x4 (Gen 3.x) slots	✓ 4 2 1.4b 4 ✓ 2		
Design		Linux operating systems supported	Mac OS V 10.7 Lion Mac OS V 10.9
Chassis type * Cooling type * Product colour Number of fans	Tower Active Black, Bronze 3 fan(s)	Mac operating systems supported Server operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Fan diameter	9 cm	Power	
Fan diameter 2	6 cm	Power supply location Power supply unit (PSU) capacity Number of power supply units AC input voltage AC input frequency Output current	Built-in 250 W 1 100 - 240 V 50 - 60 Hz 3.5 A
		Weight & dimensions	
		Width * Depth * Height *	264.3 mm 279.6 mm 188.2 mm
		Packaging content	
		Cables included Quick installation guide Number of screws	AC, LAN (RJ-45) ✓ 20
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

