



# QNAP TS-1277XU-RP NAS Rack (2U) AMD Ryzen™ 5 2600 8 GB DDR4 96 TB HDD QNAP Turbo System Black



Brand : QNAP

Product code: TS-1277XU-RP-2600-8G-96TB-GLD

Product name : TS-1277XU-RP

2U, AMD Ryzen 5 2600 3.4 GHz, 8 GB DDR4, 12x 3.5", SATA 6 Gbps, 2x 10GbE SFP+, 2x RJ45, USB 3.1, USB 3.0, 4x PCIe, 100-240V AC, 50/60Hz, 2x 300W, QTS 4.3.4

QNAP TS-1277XU-RP. Type: NAS. Chassis type: Rack (2U). Device class: Small & Medium Business. Processor family: AMD Ryzen™ 5, Processor model: 2600, Processor frequency: 3.4 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 96 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System



Storage		Design	
Supported storage drive interfaces	Serial ATA III	Fan diameter	7 cm
Storage drive sizes supported	2.5,3.5"	Fan diameter 2	7 cm
RAID support *	✓	LED indicators	✓
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Built-in display	✗
Online RAID migration	✓	Performance	
Online RAID expansion	✓	Type *	NAS
RAID rebuild	✓	Device class *	Small & Medium Business
Hot-swap drive bays	✓	Backup function *	✓
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Backup features	Cloud, iSCSI LUN
Storage drives installed *	✓	Multilingual support	✓
Total installed storage capacity *	96 TB	Third-party support	✓
Number of storage drives supported *	12	Built-in optical drive	✗
Installed storage drive type *	HDD	Card reader integrated	✗
Supported storage drive types *	HDD & SSD	Snapshot	✓
Bad block scan	✓	Management protocols	SNMP
Disk roaming	✓	Web-based management	✓
Processor		Share folder access right management	✓
Processor family *	AMD Ryzen™ 5	Security algorithms	256-bit AES, FIPS 140-2
Processor model *	2600	Access Control List (ACL)	✓
Processor frequency *	3.4 GHz	Built-in BitTorrent client	✓
Processor boost frequency	3.9 GHz	Built-in iTunes server	✓
Processor cores	6	Built-in FTP server	✓
Processor threads	12	Browser supported	Microsoft Internet Explorer 10, Mozilla Firefox, Google Chrome, Apple Safari 7+
CPU configuration (max)	1	System log	✓
Processor operating modes	64-bit	Hot spare	✓
Memory		Password authentication	✓
Internal memory *	8 GB	Disk scan	✓
Internal memory type	DDR4	S.M.A.R.T. support	✓
Maximum RAM supported	64 GB	Share folder	CIFS/SMB
Memory slots	4	Universal Plug and Play (UPnP)	✓
Memory form factor	DIMM	Software	
Network		Operating system installed *	QNAP Turbo System
Ethernet LAN *	✓	Operating system version	4.3.4
Ethernet LAN data rates	10,100,1000,10000 Mbit/s		

Network		Software	
Ethernet LAN data rate supported (max)	10000 Mbit/s	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Wi-Fi	✗	Linux operating systems supported	✓
DHCP client	✓	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
DHCP server	✓	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Jumbo frames support	✓		
iSCSI support	✓		
Wake-on-LAN ready	✓		
Supported network protocols	TCP/IP, IPv4, IPv6, NAT, STP, SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP		
Dynamic DNS (DDNS)	✓		
Ports & interfaces		Power	
USB port *	✓	Power supply location	Built-in
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Power supply unit (PSU) capacity	300 W
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1	Number of power supply units	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1	Redundant power supply (RPS) support	✓
Fiber ports quantity	2	AC input voltage	100-240 V
Fiber optic connector	SFP+	AC input frequency	50 - 60 Hz
Ethernet LAN (RJ-45) ports *	2	Fan voltage	12 V
Thunderbolt 3 ports quantity	2	Weight & dimensions	
6.35 mm (1/4-inch) input	2	Width *	482 mm
PCI Express x4 (Gen 3.x) slots	2	Depth *	562 mm
PCI Express x8 (Gen 3.x) slots	2	Height *	88.3 mm
Design		Packaging content	
Chassis type *	Rack (2U)	Cables included	AC, LAN (RJ-45)
Cooling type *	Active	Quick installation guide	✓
Product colour	Black	Number of screws	84
Number of fans	2 fan(s)	Sustainability	
		Sustainability certificates	RoHS
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Other features	
		Digital Living Network Alliance (DLNA) certified	✓
		Compliance certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-AUG-2024. Prints or copies of Information are only valid on the printed Publication date