

QNAP TS-H886 NAS Tower Ethernet LAN Black, Grey D-1622





Brand: QNAP Product code: TS-H886-D1622-16G/96TB-EXOS

Product name: TS-H886

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission
- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications
- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance
- Two PCle slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery
- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2, 231.9x292.9x319.8 mm

| | | D. C | |
|--|------------------------------------|------------------------------------|--|
| Storage | | Performance | |
| Supported storage drive interfaces | Serial ATA II, Serial ATA III | Multilingual support | ✓ |
| Storage drive sizes supported | 2.5,3.5" | Noise level | 20.4 dB |
| Number of M.2 (M & B) slots | 2 | Snapshot | ✓ |
| RAID support * | ✓ | Web-based management | ✓ |
| RAID levels Online RAID migration | 0, 1, 5, 6, 10, 50, 60 | Security algorithms | 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS |
| Online RAID expansion | 1 | Access Control List (ACL) | ✓ |
| RAID rebuild | 1 | Reset button | ✓ |
| Hot-swap drive bays | 1 | On/off switch | ✓ |
| Supported file systems | FAT32, HFS+, NTFS, ZFS, ext3, ext4 | Built-in FTP server | ✓ |
| Storage drives installed * | ✓ | Browser supported | Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, |
| Total installed storage capacity * | 96 TB | | Mozilla Firefox |
| Number of storage drives installed * | | System log | ✓ |
| Number of storage drives supported | 8 | Hot spare | ✓ |
| Installed storage drive type * | HDD | S.M.A.R.T. support | ✓ |
| Supported storage drive types * | HDD & SSD | Share folder | CIFS/SMB |
| Bad block scan | √ 33b | Universal Plug and Play (UPnP) | ✓ |
| Disk roaming | * | USB copy function | ✓ |
| | * | Software | |
| Processor | | Operating system installed * | QNAP Turbo System |
| Processor manufacturer * | Intel | Operating system version | 4.5.0 |
| Processor family * | Intel® Xeon® D | Windows operating systems | |
| Processor model * | D-1622 | supported | Windows 10, Windows 7, Windows 8 |
| Processor frequency * | 2.6 GHz | Linux operating systems supported | ✓ |
| Processor boost frequency | 3.2 GHz | | Mac OS X 10.10 Yosemite, Mac OS X |
| Processor cores | 4 | Management and a second and | 10.11 El Capitan, Mac OS X 10.12 |
| Processor threads | 8 | Mac operating systems supported | Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X |
| Processor cache | 6 MB | | 10.15 Catalina |
| CPU configuration (max) | 1 | | Windows Server 2008 R2, Windows |
| PCI Express slots version | 2.0, 3.0 | Server operating systems supported | Server 2012, Windows Server 2012 |
| Processor lithography | 14 nm | , 3, | R2, Windows Server 2016, Windows Server 2019 |
| Processor operating modes | 64-bit | _ | 56.76.72013 |
| Processor package size | 37.5 x 37.5 mm | Power | |
| Scalability | 15 | Power supply location | Built-in |
| Tcase | 83 °C | Power supply unit (PSU) capacity | 250 W |
| Tjunction | 105 °C | Number of power supply units | 1 |
| Thermal Design Power (TDP) | 40 W | Power consumption (typical) | 75.79 W |
| On-board graphics card model | Not available | AC input voltage | 100 - 240 V |
| Maximum internal memory supported by processor | 128 GB | AC input frequency | 50 - 60 Hz |

| Memory | | Weight & dimensions | |
|---|---|---|--|
| Internal memory type Maximum RAM supported Internal memory * Memory form factor | DDR4 128 GB 16 GB UDIMM | Width * Depth * Height * Weight | 292.9 mm 319.8 mm 231.9 mm 8.5 kg |
| Flash memory | 5000 MB | Packaging content | |
| Network | | Cables included | AC, LAN (RJ-45) |
| Ethernet LAN * Ethernet LAN data rates DHCP client DHCP server Jumbo frames support | 10,100,1000,2500 Mbit/s | Number of screws | 32 |
| | | Processor special features | |
| | | Embedded options available | × |
| | | Enhanced Intel SpeedStep Technology | ✓ |
| Supported network protocols | TCP/IP, HTTP/HTTPS | Execute Disable Bit | ✓ |
| Ports & interfaces | | Idle States | ✓ |
| USB port * | ✓ | Intel 64 | √ |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 3 | Intel QuickAssist Technology | × |
| ports quantity Ethernet LAN (RJ-45) ports * | 4 | Intel Trusted Execution Technology Intel TSX-NI | 4 |
| PCI Express x8 (Gen 3.x) slots | 2 | Intel Virtualization Technology (VT-x) | v |
| Design | | Intel Virtualization Technology for | , |
| Chassis type * | Tower | Directed I/O (VT-d) | • |
| Cooling type * | Active | Intel VT-x with Extended Page Tables (EPT) | ✓ |
| Product colour Number of fans Fan diameter Fan diameter 2 | Black, Grey 3 fan(s) 8 cm 9.7 cm | Intel® AES New Instructions (Intel® AES-NI) | ✓ |
| | | Intel® Hyper Threading Technology (Intel® HT Technology) | ✓ |
| LED indicators | HDD, SSD, Status | Intel® OS Guard | ✓ |
| Built-in display | V | Intel® Secure Key | ✓ |
| Cable lock slot Cable lock slot type | ✓ Kensington | Intel® Turbo Boost Technology | 2.0 |
| Performance | Kensington | Maximum number of PCI Express lanes | 32 |
| Type * | NAS | Thermal Monitoring Technologies | 1 |
| Device class * Backup function * Backup features Buzzer | Large Enterprise Business Cloud, iSCSI LUN | Memory types supported by processor | DDR3-SDRAM, DDR4-SDRAM |
| | | Operational conditions | |
| | | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 35 °C 5 - 95% |
| | | Logistics data | |
| | | Harmonized System (HS) code | 84714100 |
| | | Other features | |
| | | Processor ARK ID | 193687 |

