QNAP

QNAP TS-877XU-RP NAS Rack (2U) AMD Ryzen™ 5 2600 8 GB DDR4 96 TB HDD QNAP Turbo System Black

Brand : QNAP **Product code:** TS-877XU-RP-2600-8G-96TB-GLD

Product name: TS-877XU-RP

- $\hbox{-} Two 10 GbE SFP+ ports provide higher bandwidth to empower applications like virtualization, 4K video editing and file sharing$
- PCle expandability allows for installing 10GbE/40GbE adapters, PCle NVMe SSD, graphics cards, USB $3.1~{\rm Gen}~2~(10{\rm Gbps})$ cards, or wireless network cards
- Supports AMD Radeon™ and NVIDIA® graphics cards for video processing or GPU-passthrough to VMs
- Qtier™ technology and SSD caching enable 24/7 optimized storage efficiency
- Scalable storage supporting virtualization, containerized apps, centralized storage, backup, sharing, and disaster recovery
- RAID 50/60 is recommended for NAS with over 6 disks to strike a balance between capacity, protection, and performance
- 2U, AMD Ryzen 5 2600 3.4 GHz, 8 GB DDR4, 8x 3.5", SATA 6 Gbps, 2x 10GbE SFP+, 2x RJ45, USB 3.1, USB 3.0, 4x PCIe, 100-240V AC, 50/60Hz, 2x 300W, QTS 4.3.4





| Storage | | Design | |
|--|--|--|--|
| Supported storage drive interfaces Storage drive sizes supported RAID support * | Serial ATA III 2.5,3.5" ✓ | Fan diameter 2 LED indicators Built-in display | 7 cm ✓ × |
| RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types * Bad block scan | 0, 1, 5, 6, 10, 50, JBOD ✓ ✓ FAT32, HFS+, NTFS, exFAT, ext3, ext4 ✓ 96 TB | Performance Type * Device class * Backup function * Backup features Multilingual support Noise level Third-party support Built-in optical drive Card reader integrated Snapshot Management protocols Web-based management | NAS Small & Medium Business Cloud, iSCSI LUN 37.7 dB X NMP |
| Disk roaming Processor | 1 | Share folder access right management | ✓ |
| Processor Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor threads CPU configuration (max) Processor operating modes | AMD Ryzen™ 5 2600 3.4 GHz 3.9 GHz 6 12 1 64-bit | Security algorithms Access Control List (ACL) Built-in BitTorrent client Built-in iTunes server Built-in FTP server Browser supported System log Hot spare | 256-bit AES, FIPS 140-2 |
| Memory | | Password authentication | y |
| Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor | 8 GB DDR4 64 GB 4 DIMM | Disk scan S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) | ✓ ✓ CIFS/SMB ✓ |
| Network | Piriti | Software | |
| Ethernet LAN * Ethernet LAN data rates | 10,100,1000,10000 Mbit/s | Operating system installed * Operating system version | QNAP Turbo System 4.3.4 |

| Network | | Software | |
|---|--|--|---|
| Ethernet LAN data rate supported (max) | 10000 Mbit/s | Windows operating systems supported | Windows 10, Windows 7, Windows 8 |
| Wi-Fi | × | Linux operating systems supported | ✓ |
| DHCP client | ✓ | | Mac OS X 10.10 Yosemite, Mac OS X |
| DHCP server | ✓ | | 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, |
| Jumbo frames support | ✓ | Mac operating systems supported | Mac OS X 10.7 Lion, Mac OS X 10.8 |
| iSCSI support | ✓ | | Mountain Lion, Mac OS X 10.9 Mavericks |
| Wake-on-LAN ready | V | | Windows Server 2003, Windows |
| Supported network protocols | TCP/IP, IPv4, IPv6, NAT, STP, SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP | Server operating systems supported | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, |
| Dynamic DNS (DDNS) | 1 | | Windows Server 2016 |
| Ports & interfaces | | Power | |
| USB port * | ✓ | Power supply location | Built-in |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 4 | Power supply unit (PSU) capacity | 300 W |
| ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A | | Number of power supply units | 2 |
| ports quantity | 1 | Redundant power supply (RPS) support | ✓ |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 1 | AC input voltage | 100-240 V |
| Fiber ports quantity | 2 | AC input frequency | 50 - 60 Hz |
| Fiber optic connector | SFP+ | Fan voltage | 12 V |
| Ethernet LAN (RJ-45) ports * | 2 | Weight & dimensions | |
| PCI Express x4 (Gen 3.x) slots | 2 | Width * | 482 mm |
| PCI Express x8 (Gen 3.x) slots | 2 | Depth * | 562 mm |
| Design | | Height * | 88.3 mm |
| Chassis type * | Rack (2U) | Packaging content | |
| Cooling type * | Active | Cables included | AC, LAN (RJ-45) |
| Product colour | Black | Quick installation guide | ✓ |
| Number of fans | 2 fan(s) | Number of screws | 56 |
| Fan diameter | 7 cm | Sustainability | |
| | | Sustainability certificates | RoHS |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 40 °C |
| | | Operating relative humidity (H-H) | 5 - 95% |
| | | Other features | |
| | | Digital Living Network Alliance (DLNA) certified | 1 |
| | | Compliance certificates | RoHS |

