QNAP TS-977XU NAS Rack (1U) AMD Ryzen[™] 3 1200 8 GB DDR4 32 TB HDD QNAP Turbo System Black

Brand : QNAP

Product code: TS-977XU-1200-4G-32TB-GLD

Product name : TS-977XU

- Install up to five SSDs in the 2.5-inch drive bays to enable SSD caching and Qtier for optimal system performance

- Two 10GbE SFP+ ports provide higher bandwidth to empower applications like virtualization, 4K video editing and file sharing

- PCle expandability allows for installing QM2 expansion card, USB 3.1 Gen 2 (10Gbps) cards, or wireless network cards

- Snapshots add an extra layer of protection for disaster recovery plans. You can set a custom snapshot schedule and can use snapshots to recover data from a local or remote NAS

- Scalable storage supporting virtualization, containerized apps, centralized storage, backup, sharing, and disaster recovery

- Besides using QNAP storage expansion enclosures, you can also leverage QNAP VJBOD technology to use the unused storage space from other NAS $\,$

AMD Ryzen 3 1200 3.1 GHz, 4 GB DDR4, 4x 3.5", 5x 2.5", 2x 10G SFP+, 2x RJ-45, USB 3.1, 4x USB 3.0, PCIe 3.0 x16, 1U, PSU 250 W, 43.3x482.6x484.15 mm

Storage		Ports & interfaces	
Supported storage drive interfaces	Serial ATA III	Ethernet LAN (RJ-45) ports *	2
Storage drive sizes supported	2.5,3.5"		2
RAID support *		Design	
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Chassis type *	Rack (1U)
Online RAID migration	<pre></pre>	Cooling type *	Active
Online RAID expansion		Product colour	Black
RAID rebuild	4	Number of fans	3 fan(s)
Hot-swap drive bays	1	Fan diameter	4 cm
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Performance	
Storage drives installed *	1	Type *	NAS
Total installed storage capacity st	32 TB	Device class *	Small & Medium Business
Number of storage drives supported	١٩	Backup function *	✓
*	5	Backup features	Cloud, iSCSI LUN
Installed storage drive type *	HDD	Multilingual support	<
Supported storage drive types *	HDD & SSD	Noise level	39.2 dB
Bad block scan	4	Snapshot	<
Processor		Web-based management	<
Processor family *	AMD Ryzen™ 3	Security algorithms	256-bit AES, FIPS 140-2, HTTPS,
Processor model *	1200	Access Control List (ACL)	SNMP, SNMPv3, SSH, SSL/TLS
Processor frequency *	3.1 GHz	On/off switch	
Processor boost frequency	3.4 GHz	Built-in iTunes server	×
Processor cores	4	Built-in FTP server	<u>,</u>
Processor threads	4		Safari 7+, Chrome, Internet
Processor operating modes	64-bit	Browser supported	Explorer 10+, Firefox
Memory		System log	<
Internal memory *	8 GB	Hot spare	✓
Internal memory type	DDR4	S.M.A.R.T. support	<
Maximum RAM supported	64 GB	Share folder	CIFS/SMB
Memory slots	4	Software	
Network		Operating system installed *	QNAP Turbo System
Ethernet LAN *	4	Operating system version	4.3.4
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Windows operating systems	Windows 10, Windows 7, Windows 8
Ethernet LAN data rate supported (max)	10000 Mbit/s	supported	
Wi-Fi	×		
DHCP client	4		



Network		Software	
DHCP server / Jumbo frames support / iSCSI support / Wake-on-LAN ready / Dynamic DNS (DDNS) /	1 1 1 1	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
WLAN adapter supported	4	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Ports & interfaces			
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Power	
		Power supply location	Built-in
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1	Power supply unit (PSU) capacity	250 W
Fiber ports quantity Fiber optic connector	2 SFP+	Number of power supply units	1 100 - 240 V
		AC input voltage AC input frequency	50 - 60 Hz
		Fan voltage	12 V
		Weight & dimensions	
		Width * Depth * Height *	482.6 mm 484.1 mm 43.3 mm
		Packaging content	
		Cables included	AC, LAN (RJ-45)

Quick installation guide

Operational conditions Operating temperature (T-T)

Operating relative humidity (H-H)

Number of screws

∢

52

0 - 40 °C

5 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.