



# QNAP TS-h686 NAS Tower Ethernet LAN Black D-1602



Brand : QNAP

Product code: TS-H686-D1602-8G/8TB-REDPLUS

Product name : TS-h686

Intel Xeon D-1602 (2x 2.5GHz), 8GB DDR4, 5GB Flash, 4x 2.5"/3.5" + 2x 2.5", 2x M.2, 4x 2.5G RJ-45, 3x USB 3.2 Gen1  
QNAP TS-h686. Total installed storage capacity: 8 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: Intel® Xeon® D, Processor manufacturer: Intel, Processor model: D-1602. Internal memory: 8 GB, Internal memory type: DDR4, Maximum RAM supported: 128 GB. Ethernet LAN data rates: 10,100,1000,2500 Mbit/s. Chassis type: Tower, Cooling type: Active, Product colour: Black

Storage		Performance	
Storage drive capacity *	4 TB	Backup function *	✓
Storage drive interface *	Serial ATA II, Serial ATA III	Backup features	Cloud, iSCSI LUN
Supported storage drive interfaces	M.2, Serial ATA II, Serial ATA III	Buzzer	✓
Storage drive sizes supported	2.5,3.5,M.2	Multilingual support	✓
Number of M.2 (M & B) slots	2	Noise level	18.6 dB
RAID support *	✓	Snapshot	✓
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Management protocols	SNMP 2/3
Online RAID migration	✓	Web-based management	✓
Online RAID expansion	✓	Security algorithms	256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
RAID rebuild	✓	Access Control List (ACL)	✓
Hot-swap drive bays	✓	Reset button	✓
Supported file systems	FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4	On/off switch	✓
Storage drives installed *	✓	Built-in FTP server	✓
Total installed storage capacity *	8 TB	Browser supported	Safari, Chrome, Internet Explorer, Firefox
Number of storage drives installed *	4	System log	✓
Number of storage drives supported *	6	Hot spare	✓
Installed storage drive type *	HDD	S.M.A.R.T. support	✓
Supported storage drive types *	HDD & SSD	Share folder	CIFS/SMB
Bad block scan	✓	Universal Plug and Play (UPnP)	✓
Disk roaming	✓	USB copy function	✓
Processor		Software	
Processor manufacturer *	Intel	Operating system installed *	QuTS hero
Processor family *	Intel® Xeon® D	Operating system version	h5.0.0
Processor model *	D-1602	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Processor frequency *	2.5 GHz	Linux operating systems supported	✓
Processor boost frequency	3.2 GHz	Mac operating systems supported	✓
Processor cores	2	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Processor threads	4		
Processor cache	3 MB		
CPU configuration (max)	1		
Memory		Power	
Internal memory type	DDR4	Power supply location	Built-in
Maximum RAM supported	128 GB	Power supply unit (PSU) capacity	250 W
Memory slots	4	Number of power supply units	1
Internal memory *	8 GB	Power consumption (typical)	61.115 W
Memory form factor	UDIMM	AC input voltage	100 - 240 V
ECC	✓	Fan voltage	12 V
Flash memory	5000 MB		
Network		Weight & dimensions	
Ethernet LAN *	✓	Width *	224.9 mm
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Depth *	319.8 mm
DHCP client	✓	Height *	231.9 mm

Network		Packaging content	
DHCP server	✓	Cables included	AC, LAN (RJ-45)
Jumbo frames support	✓	Power cables quantity	1
iSCSI support	✓	Number of screws	24
Wake-on-LAN ready	✓	Drive tray key included	✓
Dynamic DNS (DDNS)	✓		
Ports & interfaces		Processor special features	
USB port *	✓	Embedded options available	✗
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Enhanced Intel SpeedStep Technology	✓
Ethernet LAN (RJ-45) ports *	4	Execute Disable Bit	✓
PCI Express x8 (Gen 3.x) slots	2	Idle States	✓
		Intel 64	✓
Design		Intel QuickAssist Technology	✗
Chassis type *	Tower	Intel Trusted Execution Technology	✓
Cooling type *	Active	Intel TSX-NI	✓
Product colour	Black	Intel Virtualization Technology (VT-x)	✓
Number of fans	2 fan(s)	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Fan diameter	9 cm	Intel VT-x with Extended Page Tables (EPT)	✓
Fan diameter 2	9.7 cm		
LED indicators	HDD, LAN, SSD, Status, USB	Operational conditions	
Built-in display	✗	Operating temperature (T-T)	0 - 40 °C
Cable lock slot	✓	Operating relative humidity (H-H)	5 - 95%
Cable lock slot type	Kensington	Storage temperature (T-T)	-20 - 70 °C
Performance		Storage relative humidity (H-H)	5 - 95%
Type *	NAS	Logistics data	
Device class *	Home & Home Office	Harmonized System (HS) code	84714100

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date