QNAP

QNAP TS-463XU NAS Rack (1U) AMD G GX-420MC 4 GB DDR3L 24 TB HDD QNAP Turbo System Black

Brand : QNAP Product code: TS-463XU-4G-24TB-GLD

Product name : TS-463XU

- $\ \ \text{Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing}$
- $\mathsf{Qtier}^{\scriptscriptstyle\mathsf{TM}}$ auto-tiering technology and SSD caching enable constant storage optimization
- Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks
- Host containerized applications and virtual machines with various operating systems
- Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery
- NAS and iSCSI-SAN (IP-SAN) unified storage solution with scalable design

Copper ethernet cabling technology 10GBASE-T, 1000BASE-T

AMD GX-420MC 2.0 GHz, 4 GB DDR3L, 512 MB DOM, 4x 2.5/3.5", 2x USB 3.0, 3x USB 2.0, 1x RJ-45 10GBASE-T, 4x RJ-45, 1x PCIe 2.0 x4, 1U + 24TB (WD Gold)





Storage		Performance	
Storage Storage drive capacity * Storage drive interface * Supported storage drive interfaces Storage drive size Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Number of storage drives supported	2.5/3.5" 2.5,3.5" 0, 1, 5, 6, 10, 50, 60, JBOD FAT32, HFS+, NTFS, ext3, ext4 24 TB 4	Performance Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Web-based management Share folder access right management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in iTunes server	NAS Home & Home Office Cloud, USB drive, iSCSI LUN 36.5 dB 256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
* Installed storage drive type * Supported storage drive types *	HDD & SSD	Built-in FTP server Browser supported	Safari 7+, Chrome, Internet Explorer 10+, Firefox
Processor Processor family * Processor model * Processor frequency * Processor cores	AMD G GX-420MC 2 GHz 4	System log Hot spare S.M.A.R.T. support Share folder Backup button	CIFS/SMB
Memory		Software	•
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory	4 GB DDR3L 16 GB 2 SO-DIMM 512 MB	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported	QNAP Turbo System 4.3.4 Windows 10, Windows 7, Windows 8 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Network		Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra,
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)	10,100,1000,10000 Mbit/s 10000 Mbit/s	muc operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks

Network		Software	
Wi-Fi DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready	X 4 4 4 7	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
		Power	
Supported network protocols	PPTP, L2TP/IPSec, OpenVPN VPN	Power supply location	Built-in
Ports & interfaces		Power supply unit (PSU) capacity	250 W
USB port * USB 2.0 ports quantity Ethernet LAN (RJ-45) ports *	√ 3 5	Number of power supply units Power consumption (typical) Power consumption (HDD standby) AC input voltage	1 50.46 W 34.06 W 100 - 240 V
Design		AC input frequency Fan voltage	50 - 60 Hz 12 V
Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators Cable lock slot Cable lock slot type	Rack (1U) Active	Weight & dimensions	12 V
	Black 2 fan(s) 4 cm ✓ Kensington	Width * Depth * Height * Weight Package weight	439 mm 499 mm 44 mm 7.58 kg 9.54 kg
		Packaging content	
		Cables included Quick installation guide	AC, LAN (RJ-45) ✓
		Sustainability	
		Sustainability certificates	RoHS
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%
		Other features	
		Compliance certificates	RoHS

