



# QNAP TVS-472XT-I3-4G/32TB-EXOS NAS/storage server Tower Ethernet LAN Black i3-8100T



**Brand :** QNAP

**Product code:** TVS-472XT-I3-4G/32TB-EXOS



**Product name :** TVS-472XT-I3-4G/32TB-EXOS

- High-speed Thunderbolt 3 with SMB protocol, allowing Mac and Windows users to collaborate on media editing
  - 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices
  - PCIe expandability allows for graphics cards or 40GbE/ 25GbE/ 10GbE adapters to increase application performance
  - Install M.2 PCIe (Gen 3 x2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency
  - 4K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K @60Hz) output
  - Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Intel Core i3-8100T, 4 GB DDR4, 4x 3.5", 2x M.2, RJ-45, Thunderbolt, PCIe, USB 3.2, HDMI, 188.2x199.3x279.6 mm

| Storage                              |                               | Design                              |  |
|--------------------------------------|-------------------------------|-------------------------------------|--|
| Storage drive interface *            | Serial ATA II, Serial ATA III | Fan diameter 2                      | 6 cm   |
| Supported storage drive interfaces   | Serial ATA II, Serial ATA III | LED indicators                      | HDD, LAN, Status, USB  |
| Storage drive size                   | 2.5/3.5"                      | Built-in display                    | ✓  |
| Storage drive sizes supported        | 2.5,3.5"                      | Display type                        | LCD  |
| Number of system drives installed    | 1                             | Cable lock slot                     | ✓  |
| System drive capacity                | 5 GB                          | Cable lock slot type                | Kensington   |
| Number of M.2 (M & B) slots          | 2                             | Performance                         |  |
| RAID support *                       | ✓                             | Type *                              | NAS  |
| RAID levels                          | 0, 1, 5, 6, 10, JBOD          | Device class *                      | Small & Medium Business                                      |
| Online RAID migration                | ✓                             | Backup function *                   | ✓  |
| Online RAID expansion                | ✓                             | Backup features                     | Cloud, iSCSI LUN   |
| RAID rebuild                         | ✓                             | Buzzer                              | ✓  |
| Hot-swap drive bays                  | ✓                             | Multilingual support                | ✓  |
| Supported file systems               | FAT32, HFS+, NTFS, ext3, ext4 | Noise level                         | 21.2 dB  |
| Storage drives installed *           | ✓                             | Security algorithms                 | 256-bit AES, HTTPS, SSL/TLS                                  |
| Total installed storage capacity *   | 32 TB                         | Access Control List (ACL)           | ✓  |
| Number of storage drives installed * | 4                             | Reset button                        | ✓  |
| Number of storage drives supported * | 4                             | On/off switch                       | ✓  |
| Installed storage drive type *       | HDD                           | Built-in FTP server                 | ✓  |
| Supported storage drive types *      | HDD & SSD                     | Browser supported                   | Mozilla Firefox, Microsoft Edge, Google Chrome, Apple Safari |
| Processor                            |                               | System log                          | ✓  |
| Processor manufacturer *             | Intel                         | Hot spare                           | ✓  |
| Processor generation                 | 8th gen Intel® Core™ i3       | S.M.A.R.T. support                  | ✓  |
| Processor family *                   | Intel® Core™ i3               | Share folder                        | CIFS/SMB   |
| Processor model *                    | i3-8100T                      | USB copy function                   | ✓  |
| Processor frequency *                | 3.1 GHz                       | Software                            |  |
| Processor cores                      | 4                             | Operating system installed *        | QNAP Turbo System  |
| Processor threads                    | 4                             | Operating system version            | 4.4.0  |
| Processor cache                      | 6 MB                          | Windows operating systems supported | Windows 10, Windows 7, Windows 8                             |
| Bus type                             | DMI3                          | Linux operating systems supported   | ✓  |
| Configurable TDP-down frequency      | 2.4 GHz                       |                                     |  |
| CPU configuration (max)              | 1                             |                                     |  |
| Number of processors supported       | 1                             |                                     |  |
| On-board graphics card model         | Intel® UHD Graphics 630       |                                     |  |
| Memory                               |                               |                                     |  |
| Internal memory type                 | DDR4                          |                                     |  |
| Maximum RAM supported                | 64 GB                         |                                     |  |

| Memory  |                                    | Software  |   |
|---|------------------------------------|---|---|
| Memory slots                                    | 2                                  |   | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur |
| Internal memory *                               | 4 GB                               |   |   |
| Memory form factor                              | SO-DIMM                            | Mac operating systems supported                         |   |
| Flash memory                                    | 5000 MB                            |   |   |
| Network   |                                    | Server operating systems supported                      |   |
| Ethernet LAN *                                  | ✓                                  |   | Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016   |
| Ethernet LAN data rates                         | 10,100,1000,2500,5000,10000 Mbit/s |   |   |
| Ethernet LAN data rate supported (max)          | 10000 Mbit/s                       |   |   |
| DHCP client                                     | ✓                                  |   |   |
| DHCP server                                     | ✓                                  |   |   |
| Jumbo frames support                            | ✓                                  |   |   |
| iSCSI support                                   | ✓                                  |   |   |
| Wake-on-LAN ready                               | ✓                                  |   |   |
| Link aggregation                                | ✓                                  |   |   |
| Load balancing system                           | ✓                                  |   |   |
| Dynamic DNS (DDNS)                              | ✓                                  |   |   |
| WLAN adapter supported                          | ✓                                  |   |   |
| Ports & interfaces                              |                                    | Power   |   |
| USB port *                                      | ✓                                  | Power supply location                                   | Built-in  |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1                                  | Power supply unit (PSU) capacity                        | 250 W   |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2                                  | Number of power supply units                            | 1   |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 2                                  | Power consumption (typical)                             | 37.32 W   |
| HDMI ports quantity                             | 1                                  | Power consumption (sleep)                               | 24.14 W   |
| HDMI version                                    | 2.0                                | AC input voltage  | 100-240 V   |
| Ethernet LAN (RJ-45) ports *                    | 3                                  | Fan voltage   | 12 V  |
| Thunderbolt 3 ports quantity                    | 2                                  |   |   |
| PCI Express x4 (Gen 3.x) slots                  | 1                                  |   |   |
| Design  |                                    | Weight & dimensions                                     |   |
| Chassis type *                                  | Tower                              | Width *   | 199.3 mm  |
| Cooling type *                                  | Active                             | Depth *   | 279.6 mm  |
| Product colour                                  | Black                              | Height *  | 188.2 mm  |
| Number of fans                                  | 3 fan(s)                           | Weight  | 5.4 kg  |
| Fan diameter                                    | 12 cm                              |   |   |
|   |                                    | Packaging content                                       |   |
|   |                                    | Cables included   | AC, LAN (RJ-45)   |
|   |                                    | Power cables quantity                                   | 1   |
|   |                                    | Processor special features                              |   |
|   |                                    | Embedded options available                              | ✓   |
|   |                                    | Enhanced Intel SpeedStep Technology                     | ✓   |
|   |                                    | Execute Disable Bit                                     | ✓   |
|   |                                    | Idle States   | ✓   |
|   |                                    | Intel 64  | ✓   |
|   |                                    | Intel Clear Video Technology                            | ✓   |
|   |                                    | Intel Enhanced Halt State                               | ✓   |
|   |                                    | Intel Identity Protection Technology version            | 1.00  |
|   |                                    | Intel Secure Key Technology version                     | 1.00  |
|   |                                    | Intel Stable Image Platform Program (SIPP)              | ✗   |
|   |                                    | Intel Stable Image Platform Program (SIPP) version      | 0.00  |
|   |                                    | Intel Trusted Execution Technology                      | ✗   |
|   |                                    | Intel TSX-NI  | ✗   |
|   |                                    | Intel TSX-NI version                                    | 0.00  |
|   |                                    | Intel Virtualization Technology (VT-x)                  | ✓   |
|   |                                    | Intel Virtualization Technology for Directed I/O (VT-d) | ✓   |
|   |                                    | Intel VT-x with Extended Page Tables (EPT)              | ✓   |
|   |                                    | Operational conditions                                  |   |
|   |                                    | Operating temperature (T-T)                             | 0 - 40 °C   |
|   |                                    | Operating relative humidity (H-H)                       | 5 - 95%   |
|   |                                    | Storage temperature (T-T)                               | -20 - 70 °C   |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date