## CyberPower PDU81405 power distribution unit (PDU) 24 AC outlet(s) 0U Black

**Brand :** CyberPower **Product code:** PDU81405

**Product name : PDU81405** 

21xC13, 3xC19, 220-240V, 50/60Hz, 16A, 1665x56x48mm, 7kg, Black CyberPower PDU81405. PDU types: Metered, Monitored, Switched, Rack capacity: 0U, Type: Singlephase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3.05 m, Certification: CE, EN 55032 Class A. Supported network protocols: IPv4/v6, SNMPv1/v3, HTTP/HTTPs, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and..., Firmware upgradeable via: USB. Nominal input voltage: 200-240 V, Maximum current: 16 A, AC input frequency: 50 / 60 Hz

Design		Power	
PDU types * Type Rack capacity *	Metered, Monitored, Switched Single-phase OU Vertical Metal Black LCD	Nominal input voltage * AC input frequency Maximum current *	200-240 V 50 / 60 Hz 16 A
Mounting Housing material Product colour Display Ports & interfaces		Weight & dimensions Width Depth Height Weight	1665 mm 56 mm 48 mm 7 kg
AC outlets quantity * Power plug AC outlet types * Serial ports quantity Ethernet LAN (RJ-45) ports	24 AC outlet(s) IEC 60309 C13 coupler, C19 coupler 1 3	Packaging data Package weight Package width Package depth Package height	8.9 kg 1895 mm 185 mm 115 mm
Features		Operational conditions	113 11111
Daisy chain LED indicators Cable length Certification	<b>√ √</b> 3.05 m CE, EN 55032 Class A	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 55 °C -15 - 60 °C 0 - 95% 0 - 95% 0 - 3500 m 0 - 15000 m
Management features			
Supported network protocols	IPv4/v6, SNMPv1/v3, HTTP/HTTPs, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and Syslog		
Firmware upgradeable Firmware upgradeable via	<b>√</b> USB		

