QNAP TS-1677XU-RP NAS Rack (3U) AMD Ryzen[™] 5 2600 8 GB DDR4 192 TB HDD QNAP Turbo System Black

Brand : QNAP

Product code: TS-1677XU-RP-2600-8G-192TB-GLD



3U, AMD Ryzen 5 2600 3.4 GHz, 8 GB DDR4, 16x 3.5", SATA 6 Gbps, 2x 10GbE SFP+, 2x RJ45, USB 3.1, USB 3.0, 4x PCIe, 100-240V AC, 50/60Hz, 2x 500W, QTS 4.3.4

QNAP TS-1677XU-RP. Type: NAS. Chassis type: Rack (3U). Device class: Small & Medium Business. Processor family: AMD Ryzen™ 5, Processor model: 2600, Processor frequency: 3.4 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 192 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System







Storage		Design	
Supported storage drive interfaces	Serial ATA III	Fan diameter 2	9.2 cm
Storage drive sizes supported	2.5,3.5"	LED indicators	<
RAID support *	4	Built-in display	×
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Performance	
Online RAID migration	1	Type *	NAS
Online RAID expansion	1	Device class *	Small & Medium Business
RAID rebuild	4	Backup function *	✓
Hot-swap drive bays	4	Backup features	Cloud, iSCSI LUN
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Multilingual support	✓
Storage drives installed *		Third-party support	1
Total installed storage capacity *	192 ТВ	Built-in optical drive	×
Number of storage drives supported		Card reader integrated	×
*	16	Snapshot	1
Installed storage drive type *	HDD	Management protocols	SNMP
Supported storage drive types *	HDD & SSD	Web-based management	✓
Bad block scan	1	Share folder access right management	4
Disk roaming	4	Security algorithms	256-bit AES, FIPS 140-2
Processor		Access Control List (ACL)	✓
Processor family *	AMD Ryzen™ 5	Built-in BitTorrent client	4
Processor model *	2600	Built-in iTunes server	1
Processor frequency *	3.4 GHz	Built-in FTP server	1
Processor boost frequency Processor cores Processor threads	3.9 GHz 4 4	Browser supported	Microsoft Internet Exploer 10, Mozilla Firefox, Google Chrome, Apple Safari 7+
CPU configuration (max)	1	System log	✓
Processor operating modes	64-bit	Hot spare	✓
Memory		Password authentication	✓
-	0.0D	Disk scan	✓
Internal memory *	8 GB	S.M.A.R.T. support	✓
Internal memory type	DDR4	Share folder	CIFS/SMB
Maximum RAM supported	64 GB 4	Universal Plug and Play (UPnP)	✓
Memory slots Memory form factor	4 DIMM	Software	
		Operating system installed *	QNAP Turbo System
Network		Operating system version	4.3.4
Ethernet LAN * Ethernet LAN data rates	✓ 10,100,1000,10000 Mbit/s	Windows operating systems supported	Windows 10, Windows 7, Windows 8

Network		Software	
Ethernet LAN data rate supported (max)100Wi-FiXDHCP clientImplement ImplementDHCP serverImplement ImplementJumbo frames supportImplement Implement	10000 Mbit/s	Linux operating systems supported Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks Windows Server 2003, Windows
Wake-on-LAN ready Supported network protocols	TCP/IP, IPv4, IPv6, NAT, STP, SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP	Server operating systems supported	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Dynamic DNS (DDNS)	4	Power	
Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity Fiber ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * PCI Express x4 (Gen 3.x) slots PCI Express x8 (Gen 3.x) slots	 ✓ 4 1 1 2 SFP+ 2 2 2 2 	Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support AC input voltage AC input frequency Fan voltage Weight & dimensions Width * Depth * Height *	Built-in 500 W 2 ✓ 100 - 240 V 50 - 60 Hz 12 V ✓ 481 mm 573.5 mm 130 mm
Design		Packaging content	
Chassis type * Cooling type * Product colour Number of fans	Rack (3U) Active Black 2 fan(s) 9.2 cm	Cables included Quick installation guide Number of screws Sustainability	AC, LAN (RJ-45) ✓ 128
		Sustainability certificates	RoHS
i an diameter	9.2 Cm		
		Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%
		Other features	
		Digital Living Network Alliance (DLNA) certified	4

Compliance certificates

RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.