

NETGEAR GS724TP-300EUS network switch Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Blue

Brand : NETGEAR

Product code: GS724TP-300EUS



Product name : GS724TP-300EUS

24-Port Gigabit Ethernet PoE+, 24-port RJ-45, PoE, 512Kb, 380W
NETGEAR GS724TP-300EUS. Switch type: Managed, Switch layer: L2/L3/L4. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 8000 entries, Switching capacity: 52 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3z. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting



Management features		Security	
Switch type *	Managed	SSH/SSL support	✓
Switch layer	L2/L3/L4	Multicast features	
Quality of Service (QoS) support	✓	Multicast support	✓
Web-based management	✓	Number of multicast groups filtered	128
System event log	✓	Protocols	
Ports & interfaces		Management protocols	SNMP v1/v2/v3
Basic switching RJ-45 Ethernet ports quantity *	24	Design	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Rack mounting *	✓
SFP module slots quantity	2	Stackable *	✓
Power connector	DC-in jack	Product colour	Blue
Network		LED indicators	Activity, Link, Speed
Networking standards *	IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3z	Number of fans	3 fan(s)
10G support *	✓	Certification	CE, FCC, VCCI, EN, C-Tick, CCC, CSA, UL/cUL, IEC
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 100BASE-TX, 1000BASE-T	Performance	
Port mirroring	✓	Firmware upgradeable	✓
Full duplex	✓	Mean time between failures (MTBF)	634966 h
IP routing	✓	Power	
Flow control support	✓	Power supply included *	✓
Link aggregation	✓	AC input voltage	100 - 240 V
Broadcast storm control	✓	Power consumption (max)	446.7 W
Spanning tree protocol	✓	Power over Ethernet (PoE)	
VLAN support	✓	Power over Ethernet (PoE) *	✓
Number of VLANs	64	Total Power over Ethernet (PoE) budget	380 W
Optical fiber		Operational conditions	
Fiber ethernet cabling technology	1000BASE-LX, 1000BASE-SX	Operating temperature (T-T)	0 - 50 °C
Data transmission		Storage temperature (T-T)	-20 - 70 °C
Switching capacity *	52 Gbit/s	Operating relative humidity (H-H)	0 - 90%
MAC address table *	8000 entries	Storage relative humidity (H-H)	0 - 95%
Store-and-forward	✓	Operating altitude	0 - 3000 m
Number of queues	8	Weight & dimensions	
Number of static routes	32	Width	440 mm
Jumbo frames support	✓	Depth	204 mm
Jumbo frames	9216	Height	43 mm
		Weight	3.7 kg

Data transmission		Packaging data	
Packet buffer memory	0.512 MB	Cables included	AC
Security		Quick start guide	✓
DHCP features	DHCP client	User guide	✓
Access Control List (ACL)	✓	Manual	✓
IGMP snooping	✓		
Security algorithms	802.1x RADIUS, HTTPS, SSL/TLS		
MAC address filtering	✓		



0606449162660



606449162660



(01)10606449162667

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.