QNAP

QNAP TS-1677XU-RP NAS Rack (3U) AMD Ryzen™ 5 2600 8 GB **DDR4 128 TB HDD QNAP Turbo System Black**

Brand: QNAP Product code: TS-1677XU-RP-2600-8G-128TB-GLD



Product name : TS-1677XU-RP

3U, AMD Ryzen 5 2600 3.4 GHz, 8 GB DDR4, 16x 3.5", SATA 6 Gbps, 2x 10GbE SFP+, 2x RJ45, USB 3.1, USB 3.0, 4x PCle, 100-240V AC, 50/60Hz, 2x 500W, QTS 4.3.4

QNAP TS-1677XU-RP. Type: NAS. Chassis type: Rack (3U). Device class: Small & Medium Business. Processor family: AMD Ryzen™ 5, Processor model: 2600, Processor frequency: 3.4 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 128 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System









Storage		Design	
Supported storage drive interfaces	Serial ATA III	Fan diameter 2	9.2 cm
Storage drive sizes supported	2.5,3.5"	LED indicators	✓
RAID support *	✓	Built-in display	×
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Performance	
Online RAID migration	✓	Type *	NAS
Online RAID expansion	✓	Device class *	Small & Medium Business
RAID rebuild	✓	Backup function *	Jiliali & Mediulii busiiless
Hot-swap drive bays	✓	·	Cloud, iSCSI LUN
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Backup features Multilingual support	✓
Storage drives installed *	✓	Third-party support	✓
Total installed storage capacity *	128 TB	Built-in optical drive	×
Number of storage drives supported	16	Card reader integrated	×
*	10	Snapshot	✓
Installed storage drive type *	HDD	Management protocols	SNMP
Supported storage drive types *	HDD & SSD	Web-based management	✓
Bad block scan Disk roaming	√	Share folder access right management	✓
J The state of the		Security algorithms	256-bit AES, FIPS 140-2
Processor		Access Control List (ACL)	✓
Processor family *	AMD Ryzen™ 5	Built-in BitTorrent client	✓
Processor model *	2600	Built-in iTunes server	✓
Processor frequency *	3.4 GHz	Built-in FTP server	✓
Processor boost frequency Processor cores	3.9 GHz 4	Browser supported	Microsoft Internet Exploer 10, Mozilla Firefox, Google Chrome, Apple Safari 7+
Processor threads	4	System log	✓
CPU configuration (max)	1	Hot spare	1
Processor operating modes	64-bit	Password authentication	1
Memory		Disk scan	,
Internal memory *	8 GB	S.M.A.R.T. support	,
Internal memory type	DDR4	Share folder	CIFS/SMB
Maximum RAM supported	64 GB	Universal Plug and Play (UPnP)	✓
Memory slots	4		▼
Memory form factor	DIMM	Software	
Network		Operating system installed *	QNAP Turbo System
Ethernet LAN *	✓	Operating system version	4.3.4
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Windows operating systems supported	Windows 10, Windows 7, Windows

Network		Software	
			,
Ethernet LAN data rate supported (max) Wi-Fi DHCP client DHCP server Jumbo frames support	10000 Mbit/s X ✓	Linux operating systems supported Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
iSCSI support Wake-on-LAN ready Supported network protocols	✓ ✓ TCP/IP, IPv4, IPv6, NAT, STP, SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Dynamic DNS (DDNS)	V	Power	
Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * PCI Express x4 (Gen 3.x) slots PCI Express x8 (Gen 3.x) slots	 ✓ 4 1 2 SFP+ 2 4 4 5 7 8 9 <l< td=""><td>Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support AC input voltage AC input frequency Fan voltage Weight & dimensions Width * Depth * Height *</td><td>Built-in 500 W 2 100 - 240 V 50 - 60 Hz 12 V 481 mm 573.5 mm 130 mm</td></l<>	Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support AC input voltage AC input frequency Fan voltage Weight & dimensions Width * Depth * Height *	Built-in 500 W 2 100 - 240 V 50 - 60 Hz 12 V 481 mm 573.5 mm 130 mm
Design Chassis type * Cooling type * Product colour Number of fans	Rack (3U) Active Black 2 fan(s)	Packaging content Cables included Quick installation guide Number of screws Sustainability	AC, LAN (RJ-45) ✓ 128
Fan diameter	9.2 cm	Sustainability certificates	RoHS
Tan danietei	5.2 Cm	Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Other features	0 - 40 °C 5 - 95%
		Digital Living Network Alliance (DLNA) certified Compliance certificates	√ RoHS

