



LevelOne RJ45 to SC Fast Ethernet Media Converter, Single-Mode Fiber, 20km

Brand : LevelOne

Product code: FVT-2201

Product name : RJ45 to SC Fast Ethernet Media Converter, Single-Mode Fiber, 20km

1 x 10/100Base-TX, 1 x 100Base-FX, SC, 20 km, 1310 nm, 420 g
LevelOne RJ45 to SC Fast Ethernet Media Converter, Single-Mode Fiber, 20km. Maximum data transfer rate: 100 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, Converter output interface: 100Base-FX. Fiber optic connector: SC, Connectivity technology: Wired. Maximum transfer distance: 20000 m, Wavelength: 1310 nm, Fiber mode structure: Single-mode. LED indicators: Activity, Link, Power, Product colour: Black, Country of origin: China. Input voltage: 5 V, Input current: 1 A



Network		Design	
Maximum data transfer rate *	100 Mbit/s	Product colour	Black
Converter input interface	10Base-T, 100Base-TX	Country of origin	China
Converter output interface	100Base-FX	Certification	FCC, CE
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Power	
Ethernet interface type	Fast Ethernet	Input voltage	5 V
Ethernet LAN data rates	10,100 Mbit/s	Input current	1 A
Flow control support	✓	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	94 mm
Auto-negotiation	✓	Depth	70 mm
Store-and-forward	✓	Height	25 mm
Duplex system	Full, Half	Weight	420 g
Link Loss Carry Forward (LLCF) supported	✓	Operational conditions	
Link Loss Return (LLR) supported	✓	Operating temperature (T-T)	-40 - 75 °C
Ports & interfaces		Storage temperature (T-T)	-10 - 55 °C
Connectivity technology	Wired	Operating relative humidity (H-H)	5 - 90%
Ethernet LAN (RJ-45) ports	1	Packaging data	
Fiber ports quantity	1	Package width	235 mm
Fiber optic connector *	SC	Package depth	125 mm
Performance		Package height	55 mm
Maximum transfer distance *	20000 m	Package weight	494 g
Wavelength *	1310 nm	Package type	Box
Fiber mode structure	Single-mode	Packaging content	
Fiber cable diameters supported (core/cladding)	8.3/125,9/125,10/125 µm	AC adapter included	✓
Quick installation guide		Quick installation guide	✓
Design		Technical details	
Internal *	✗	Sustainability certificates	RoHS
LED indicators	Activity, Link, Power	Compliance certificates	RoHS
Logistics data			
Harmonized System (HS) code	85176990		



4015867185155



5050914833022



0846359031278



846359031278



8463590312786

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.