QNAP

QNAP TS-h973AX NAS Tower Ryzen Embedded V1500B 8 GB DDR4 60 TB HDD QuTS hero Black

Brand : QNAP **Product code:** TS-H973AX-8G/60TB-REDPLUS

Product name: TS-h973AX

AMD Ryzen Embedded V1500B (4x 2.2GHz), 8GB DDR4, 5GB Flash, 5x 2.5"/3.5" SATA, 4x 2.5" SATA, LAN, USB

QNAP TS-h973AX. Type: NAS. Chassis type: Tower. Device class: Home & Home Office. Processor family: Ryzen Embedded, Processor model: V1500B, Processor frequency: 2.2 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 60 TB, Installed storage drive type: HDD. Operating system installed: QuTS hero







	Performance	
18 TB	Type *	NAS
Serial ATA II, Serial ATA III	Device class *	Home & Home Office
Serial ATA II, Serial ATA III	Backup function *	✓
2.5/3.5"	Backup features	Cloud, iSCSI LUN
2.5,3.5"	Buzzer	√
✓	Multilingual support	√
0, 1, 5, 6, 10, 50, 60, JBOD	Number of users	2000 user(s)
✓	Noise level	22.9 dB
✓	Third-party support	4
✓	Snapshot	✓
✓	Management protocols	SNMP
FAT32, HFS+, NTFS, ZFS, exFAT,	Web-based management	✓
	Share folder access right	1
	management	
**	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
	Access Control List (ACL)	J301, 33L/1L3
9	• • •	V
HDD		4
		4
		1
		1
*	Duit-iii i ii server	Safari, Chrome, Internet Explorer,
	Browser supported	Firefox
AMD	System log	1
Ryzen Embedded	Hot spare	√
V1500B	Password authentication	√
2.2 GHz	Disk scan	√
4	S.M.A.R.T. support	√
	Share folder	AFP, CIFS/SMB, FTP, WebDAV
8 GB	USB copy function	✓
	Software	
64 GB		OuTS have
J. J.	Operating system installed *	QuTS hero
2	O	L
2 SO-DIMM	Operating system version	h5.0.0
2 SO-DIMM ✓	Operating system version Windows operating systems supported	h5.0.0 Windows 10, Windows 7, Windows
	Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III 2.5/3.5" 2.5,3.5" 0, 1, 5, 6, 10, 50, 60, JBOD FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 60 TB 5 9 HDD HDD & SSD AMD Ryzen Embedded V1500B 2.2 GHz 4 8 GB DDR4	Type * Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III 2.5/3.5" Backup features 2.5,3.5" Multilingual support Number of users Noise level Third-party support Snapshot Management protocols Management protocols FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 Management Security algorithms Security algorithms Access Control List (ACL) Reset button On/off switch HDD On/off switch HDD & SSD Built-in BitTorrent client Multilingual support Management Share folder access right management Security algorithms Security algorithms Security algorithms System log HDD AV media server Whose supported AMD Ryzen Embedded V1500B Password authentication Disk scan 4 S.M.A.R.T. support Share folder USB copy function Software

Network		Software	
Ethernet LAN *	✓	Mac operating systems supported	✓
Ethernet LAN data rates Ethernet LAN data rate supported (max)	ernet LAN data rate supported 10000 Mbit/s	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
DHCP client	√	Other operating systems supported	✓
DHCP server Jumbo frames support	*	Power	
iSCSI support	4	Power supply location	External
Wake-on-LAN ready	Ž.	Power supply unit (PSU) capacity	120 W
Link aggregation Load balancing system	1	Number of power supply units Power consumption (typical)	1 55.41 W
Dynamic DNS (DDNS) WLAN adapter supported	1	Power consumption (HDD standby) AC input voltage	41.2 W 100 - 240 V
Ports & interfaces		Fan voltage	12 V
USB port *	✓	Weight & dimensions	
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	3	Width * Depth *	224.6 mm 224.1 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1	Height *	182.7 mm
Ethernet LAN (RJ-45) ports *	3	Packaging content	
Design		External power adapter	✓
Chassis type *	Tower	Cables included	AC, LAN (RJ-45)
Cooling type *	Active	Power cables quantity	1
Product colour	Black	Number of screws	56
Number of fans	1 fan(s)	Operational conditions	
Fan diameter	14 cm	Operating temperature (T-T)	0 - 40 °C
Drive bay locking	✓	Operating relative humidity (H-H)	5 - 95%
LED indicators	HDD, LAN, Power, SSD, Status, USB	Storage temperature (T-T)	-20 - 70 °C
Cable lock slot	✓	Storage relative humidity (H-H)	5 - 95%
Cable lock slot type	Kensington	Logistics data	
		Harmonized System (HS) code	84714100

