## QNAP

## QNAP TS-873 NAS Tower AMD Embedded R-Series SoC RX-421ND 4 GB DDR4 16 TB HDD QNAP Turbo System Black

**Brand**: QNAP **Product code**: TS-873-4G-16TB-GLD

**Product name:** TS-873

- Two PCIe Gen3 x4 slots support QM2 cards, 10GbE adapters, or wireless network cards
- Supports the NVIDIA® GeForce® GT1030 graphics card, allowing for 4K video transcoding and output
- Dual M.2 SATA 6 Gb/s SSD slots allow for setting up caching or storage pools, improving file access efficiency
- Qtier™ auto-tiering technology and SSD caching enable 24/7 optimized storage efficiency
- Scalable storage supporting virtualization, containerized apps, centralized storage, backup, sharing, and disaster recovery
- Snapshots fully record system status and data. If files are accidentally deleted or modified, you can quickly restore the data from a snapshot

AMD R RX-421ND (4 x 2.1GHz), DDR4, 2 x PCle3.0 x4, 8 x SATA3 2.5"/3.5", 4 x USB 3.0, 4 x RJ-45







| Storage   |  | Design   |   |
|---|--|--|---|
| Supported storage drive interfaces  | Serial ATA, Serial ATA II, Serial ATA III                                  | Cable lock slot Cable lock slot type   | ✓<br>Kensington   |
| Storage drive sizes supported RAID support *  | 2.5,3.5"<br>✓  | Performance  |   |
| RAID levels Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types *  Processor | HDD<br>HDD & SSD   | Type * Device class * Backup function * Backup features Multilingual support Noise level Web-based management Share folder access right management Security algorithms Access Control List (ACL) | NAS Home & Home Office  ✓ Cloud, USB drive, iSCSI LUN  ✓ 23.4 dB  ✓ ✓ 256-bit AES, FIPS 140-2, HTTPS, SNMP, SSH, SSL/TLS  ✓ |
| Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor operating modes  | AMD Embedded R-Series SoC<br>RX-421ND<br>2.1 GHz<br>3.4 GHz<br>4<br>64-bit | Reset button On/off switch Built-in iTunes server Built-in FTP server Browser supported  | Internet Explorer 10, Firefox 8, Safari 4, Google Chrome  |
| Memory Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor   | 4 GB<br>DDR4<br>64 GB<br>4<br>SO-DIMM                                      | System log Hot spare Password authentication S.M.A.R.T. support Share folder Universal Plug and Play (UPnP)  | ✓<br>✓<br>✓<br>CIFS/SMB   |
| Flash memory  | 512 MB   | Software   |   |
| Network   |  | Operating system installed *   | QNAP Turbo System   |
| Ethernet LAN * Ethernet LAN data rates Wi-Fi DHCP client DHCP server Jumbo frames support iSCSI support   | ✓<br>10,100,1000 Mbit/s<br>×<br>✓<br>✓                                     | Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported   | 4.3.4 Windows 10, Windows 7, Windows 8  |

| Network   |  | Software   |  |
|---|--|--|--|
| Wake-on-LAN ready Supported network protocols   | IFS/SMB, AFP (v3.3), NFS(v3), FTP, FTPS, SFTP, TFTP, HTTP(S), Telnet, SSH, iSCSI, SNMP, SMTP, SMSC | Server operating systems supported   | Windows Server 2003, Windows<br>Server 2008 R2, Windows Server<br>2012, Windows Server 2012 R2,<br>Windows Server 2016 |
| Dynamic DNS (DDNS)  | ✓  | Power  |  |
| Ports & interfaces  |  | Power supply location  | Built-in   |
| USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ethernet LAN (RJ-45) ports * | 3.2 Gen 1 (3.1 Gen 1) Type-A quantity rnet LAN (RJ-45) ports * 4 phone in vin/out                  | Power supply unit (PSU) capacity  Number of power supply units  AC input voltage  AC input frequency | 250 W<br>1<br>100 - 240 V<br>50 - 60 Hz  |
| Microphone in   |  | Weight & dimensions  |  |
| Audio in/out PCI Express x4 (Gen 3.x) slots   |  | Width * Depth *  | 329.3 mm<br>279.6 mm   |
| Design  |  | Height *   | 188.2 mm   |
| Chassis type * Cooling type * Product colour Number of fans Fan diameter                | Tower Active Black 3 fan(s) 12 cm 6 cm   | Packaging content Cables included Quick installation guide Number of screws                          | AC, LAN (RJ-45)<br>✓ 26  |
| Fan diameter 2  |  | Operational conditions   |  |
| LED indicators<br>Built-in display  |  | Operating temperature (T-T) Operating relative humidity (H-H)  | 0 - 40 °C<br>5 - 95%   |
|   |  | Other features   |  |
|   |  | Digital Living Network Alliance (DLNA) certified   | ✓  |

