QNAP

Product name: TS-432PXU-2G

QNAP TS-432PXU-2G NAS Rack (1U) Annapurna Labs Alpine AL-324 2 GB DDR4 56 TB HDD Black

Brand : QNAP **Product code:** TS-432PXU-2G/56TB-EXOS

10000 1000 15 1521 NO 20/501 B 2/40

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google $^{\text{m}}$ G Suite and Microsoft 365 $^{\text{m}}$
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-432PXU by installing a compatible PCle card
- Increase the storage capacity of the TS-432PXU with QNAP TR RAID expansion enclosures or TL JBOD 4x 3.5", 2GB DDR3, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 250W PSU, 44x439x499 mm



Storage		Design	
-	Serial ATA II, Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, JBOD ✓	Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators	Rack (1U) Active Black 2 fan(s) 4 cm HDD, LAN, Status
RAID rebuild	✓	Performance	
Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types *		Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Web-based management	NAS Small & Medium Business Cloud, iSCSI LUN
Bad block scan	√	Security algorithms	256-bit AES, FIPS 140-2, HTTPS,
Processor		Access Control List (ACL)	SSH, SSL/TLS ✓
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor cores	Annapurna Labs Annapurna Labs Alpine AL-324 1.7 GHz	Reset button On/off switch Built-in FTP server Browser supported	Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+,
Memory		System log	Google Chrome
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor	2 GB DDR4 16 GB 1 UDIMM 512 MB	Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) USB copy function	✓ ✓ CIFS/SMB ✓
Flash memory	312 MD	Software	
Network Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)	100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system version Windows operating systems supported Linux operating systems supported	4.4.3 Windows 10, Windows 7, Windows 8 ✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
DHCP client DHCP server Jumbo frames support iSCSI support	4 4 4	Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina

Network		Software	
Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system WLAN adapter supported	PPTP, L2TP/IPSec, OpenVPN, QBelt	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * 2	✓	Power supply location Power supply unit (PSU) capacity Number of power supply units	Built-in 250 W 1
	2 SFP+	AC input voltage Fan voltage	100 - 240 V 12 V
		Weight & dimensions	
		Width * Depth * Height * Weight	439 mm 499 mm 44 mm 6.53 kg
		Packaging content	
		Cables included Number of screws	AC, LAN (RJ-45) 28
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

