



QNAP TS-463XU-RP NAS Rack (1U) AMD G GX-420MC 4 GB DDR3L 24 TB HDD QNAP Turbo System Black



Brand : QNAP

Product code: TS-463XU-RP-4G-24TB-GLD

Product name : TS-463XU-RP

- Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing
 - Qtier™ auto-tiering technology and SSD caching enable constant storage optimization
 - Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks
 - Host containerized applications and virtual machines with various operating systems
 - Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery
 - NAS and iSCSI-SAN (IP-SAN) unified storage solution with scalable design
- AMD GX-420MC 2.0 GHz, 4 GB DDR3L, 512 MB DOM, 4x 2.5/3.5", 2x USB 3.0, 3x USB 2.0, 1x RJ-45 10GBASE-T, 4x RJ-45, 1x PCIe 2.0 x4, 1U + 24TB (WD Gold)

Storage		Performance	
Storage drive capacity *	6 TB	Type *	NAS
Storage drive interface *	Serial ATA III	Device class *	Home & Home Office
Supported storage drive interfaces	Serial ATA III	Backup function *	✓
Storage drive size	2.5/3.5"	Backup features	Cloud, USB drive, iSCSI LUN
Storage drive sizes supported	2.5,3.5"	Buzzer	✓
RAID support *	✓	Multilingual support	✓
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Noise level	36.4 dB
Online RAID migration	✓	Web-based management	✓
Online RAID expansion	✓	Share folder access right management	✓
Hot-swap drive bays	✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Access Control List (ACL)	✓
Storage drives installed *	✓	Reset button	✓
Total installed storage capacity *	24 TB	On/off switch	✓
Number of storage drives installed *	4	Built-in iTunes server	✓
Number of storage drives supported *	4	Built-in FTP server	✓
Installed storage drive type *	HDD	Browser supported	Safari 7+, Chrome, Internet Explorer 10+, Firefox
Supported storage drive types *	HDD & SSD	System log	✓
Bad block scan	✓	Hot spare	✓
Processor		S.M.A.R.T. support	✓
Processor family *	AMD G	Share folder	CIFS/SMB
Processor model *	GX-420MC	Universal Plug and Play (UPnP)	✓
Processor frequency *	2 GHz	Software	
Processor cores	4	Operating system installed *	QNAP Turbo System
Memory		Operating system version	4.3.4
Internal memory *	4 GB	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Internal memory type	DDR3L	Linux operating systems supported	✓
Maximum RAM supported	16 GB	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Memory slots	2		
Memory form factor	SO-DIMM		
Flash memory	512 MB		
Network			
Ethernet LAN *	✓		
Ethernet LAN data rates	10,100,1000,10000 Mbit/s		
Ethernet LAN data rate supported (max)	10000 Mbit/s		

Network		Software	
Copper ethernet cabling technology	10GBASE-T, 1000BASE-T	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Wi-Fi	✗		
DHCP server	✓		
Jumbo frames support	✓		
iSCSI support	✓		
Wake-on-LAN ready	✓		
Supported network protocols	PPTP, L2TP/IPSec, OpenVPN VPN		
Ports & interfaces		Power	
USB port *	✓	Power supply location	Built-in
USB 2.0 ports quantity	3	Power supply unit (PSU) capacity	250 W
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Number of power supply units	2
Ethernet LAN (RJ-45) ports *	5	Redundant power supply (RPS) support	✓
Design		Power consumption (typical)	65.62 W
Chassis type *	Rack (1U)	Power consumption (HDD standby)	44.9 W
Cooling type *	Active	AC input voltage	100 - 240 V
Product colour	Black	AC input frequency	50 - 60 Hz
Number of fans	2 fan(s)	Fan voltage	12 V
Fan diameter	4 cm	Weight & dimensions	
LED indicators	HDD, LAN, USB	Width *	439 mm
Cable lock slot	✓	Depth *	499 mm
Cable lock slot type	Kensington	Height *	44 mm
		Weight	9.3 kg
		Package weight	11.3 kg
		Packaging content	
		Cables included	AC, LAN (RJ-45)
		Quick installation guide	✓
		Sustainability	
		Sustainability certificates	RoHS
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Other features	
		Compliance certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-AUG-2024. Prints or copies of Information are only valid on the printed Publication date