QNAP

QNAP TS-673 NAS Tower AMD Embedded R-Series SoC RX-421ND 4 GB DDR4 6 TB HDD QNAP Turbo System Black

Brand : QNAP Product code: TS-673-4G-6TB-GLD

Product name: TS-673

- Two PCIe Gen3 x4 slots support QM2 cards, 10GbE adapters, or wireless network cards
- Supports the NVIDIA® GeForce® GT1030 graphics card, allowing for 4K video transcoding and output
- Dual M.2 SATA 6 Gb/s SSD slots allow for setting up caching or storage pools, improving file access efficiency
- Qtier™ auto-tiering technology and SSD caching enable 24/7 optimized storage efficiency
- Scalable storage supporting virtualization, containerized apps, centralized storage, backup, sharing, and disaster recovery
- Snapshots fully record system status and data. If files are accidentally deleted or modified, you can quickly restore the data from a snapshot

AMD R RX-421ND (4 x 2.1GHz), 4 GB DDR4, 512 MB DOM, 2 x PCle3.0 x4, 6 x SATA3 2.5"/3.5", 4 x USB 3.0, $4 \times R_J$ -45







Storage		Design	
Supported storage drive interfaces	Serial ATA, Serial ATA II, Serial ATA III	Cable lock slot Cable lock slot type	✓ Kensington
Storage drive sizes supported RAID support *	2.5,3.5" ✓	Performance	
RAID levels Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types * Processor Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores	0, 1, 5, 6, 10, JBOD ✓ FAT32, HFS+, NTFS, exFAT, ext3, ext4 ✓ 6 TB 6 HDD HDD & SSD AMD Embedded R-Series SoC RX-421ND 2.1 GHz 3.4 GHz 4	Type * Device class * Backup function * Backup features Multilingual support Noise level Web-based management Share folder access right management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in iTunes server Built-in FTP server	NAS Home & Home Office Cloud, USB drive, iSCSI LUN 33 dB 256-bit AES, FIPS 140-2, HTTPS, SNMP, SSH, SSL/TLS
Memory		Browser supported	Internet Explorer 10, Firefox 8, Safari 4, Google Chrome
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory	4 GB DDR4 64 GB 4 SO-DIMM 512 MB	System log Hot spare Password authentication S.M.A.R.T. support Share folder Universal Plug and Play (UPnP)	✓ ✓ ✓ CIFS/SMB
Network		Software	
Ethernet LAN * Ethernet LAN data rates Wi-Fi DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready	✓ 10,100,1000 Mbit/s × ✓	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported	QNAP Turbo System 4.3.4 Windows 10, Windows 7, Windows 8 ✓

Network		Software	
Supported network protocols Dynamic DNS (DDNS)	IFS/SMB, AFP (v3.3), NFS(v3), FTP, FTPS, SFTP, TFTP, HTTP(S), Telnet, SSH, iSCSI, SNMP, SMTP, SMSC ✓	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9
Ports & interfaces			Mavericks
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ethernet LAN (RJ-45) ports * 4	4	Server operating systems supporte	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
	✓	Power	
Microphone in Audio in/out PCI Express x4 (Gen 3.x) slots		Power supply location Power supply unit (PSU) capacity	Built-in 250 W
Design		Number of power supply units AC input voltage	1 100 - 240 V
Chassis type *	Tower Active	AC input frequency	50 - 60 Hz
Cooling type *		Weight & dimensions	
Product colour Black Number of fans 3 fan(s) Fan diameter 9 cm Fan diameter 2 6 cm	3 fan(s)	Width * Depth * Height *	264.3 mm 279.6 mm 188.2 mm
LED indicators	√	Packaging content	
Built-in display	✓	Cables included Quick installation guide Number of screws	AC, LAN (RJ-45) ✓ 20
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%
		Other features	
		Digital Living Network Alliance (DLNA) certified	✓

