## **NETGEAR ProSAFE GS724Tv4 Managed L3 Gigabit Ethernet** (10/100/1000) Blue

**Brand:** NETGEAR Product code: GS724T-400EUS

**Product name:** ProSAFE GS724Tv4

24 x 10/100/1000, 2 x SFP, QoS, SNMP, L3, Blue

NETGEAR ProSAFE GS724Tv4. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 16000 entries, Switching capacity: 52 Gbit/s. Networking standards: IEEE 802.1ab, IEEE 802.1as, IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE.... Power connector: DC-in jack. Rack mounting



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L3	Number of multicast groups filtered	512
Quality of Service (QoS) support	<b>√</b>	Protocols	
Web-based management	1	Management protocols	SNMP v1/v2
System event log	*	Supported network protocols	IP
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	24	Rack mounting *	<b>√</b>
Basic switching RJ-45 Ethernet ports		Stackable *	<b>√</b>
type *	Gigabit Ethernet (10/100/1000)	Product colour	Blue
SFP module slots quantity	2	LED indicators	Activity, Link
Power connector	DC-in jack	Certification	CE, FCC, VCCI, EN, C-Tick, CCC,
Network			CSA, UL/cUL, IEC
	IEEE 802.1ab, IEEE 802.1as, IEEE	Performance	
Networking standards *	802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3z	Firmware upgradeable	✓
		Mean time between failures (MTBF)	567680 h
10G support *	✓	Power	
• •	1000BASE-T, 100BASE-T, 100BASE-	AC input voltage	100 - 240 V
Copper ethernet cabling technology	TX, 10BASE-T	AC input frequency	50 - 60 Hz
Port mirroring	✓	Power consumption (typical)	17.4 W
Full duplex	<b>V</b>	Power over Ethernet (PoE)	
IP routing	<b>V</b>	Power over Ethernet (PoE) *	×
Flow control support	<b>*</b>	. ,	~
Broadcast storm control Spanning tree protocol	<b>4</b>	Operational conditions	
VLAN support	1	Operating temperature (T-T)	0 - 50 °C
Number of VLANs	15	Storage temperature (T-T)	-20 - 70 °C
		Operating relative humidity (H-H)	0 - 90% 0 - 95%
Optical fiber	1000010517 10000105 67	Storage relative humidity (H-H) Operating altitude	0 - 3000 m
Fiber ethernet cabling technology	1000BASE-LX, 1000BASE-SX		3000111
Data transmission		Weight & dimensions	
Switching capacity *	52 Gbit/s	Width	440 mm
MAC address table *	16000 entries	Depth	204 mm
Number of queues	8	Height	43 mm
Number of static routes	32	Weight	2.74 kg
Packet buffer memory	2 MB	Packaging data	
Security		Cables included	AC
DHCP features	DHCP client	Manual	✓
Differ leatures			

SecurityIGMP snooping✓Harmonized System (HS) code85176990Security algorithmsHTTPS, SSL/TLSMAC address filtering✓SSH/SSL support✓





606449098310

0606449098310

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.