



LevelOne PoE Repeater, 2 PoE Outputs, 802.3at/af PoE

Brand : LevelOne

Product code: POR-0103

Product name : PoE Repeater, 2 PoE Outputs, 802.3at/af PoE



PoE Repeater, 2 PoE Outputs, 46-57V, 2.5W max, IEEE 802.3af/at

LevelOne PoE Repeater, 2 PoE Outputs, 802.3at/af PoE:

For system integrators looking for a professional solution to help extend their PoE network, POR-0103 is the perfect accessory to increase your Power over Ethernet network performance. LevelOne POR-0103, a 2-Port PoE Repeater requiring neither configuration nor electrical power, is an innovative transmitter to pass on both data and power extend to another 100 meters. It delivers both data and power to two PoE network devices such as WLAN Access Points, Network Cameras and other appliances with fast speed to the network for greater deployment flexibility.



- High Power Midspan PoE compliant to simplify deployment and installation
- Built-in 2 PoE output ports for PoE devices
- 10/100Mbps wire speed transmission and reception
- Forwards Power over Ethernet to remote device
- Extends PoE connection for another 100 meters
- Simple Plug and Play installation, no additional power supply required



Performance		Operational conditions	
Type *	Network repeater	Storage temperature (T-T)	-20 - 70 °C
Maximum transfer distance *	100 m	Operating relative humidity (H-H)	5 - 95%
Network		Storage relative humidity (H-H)	5 - 95%
Cabling technology	10/100Base-T(X)	Weight & dimensions	
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	Width	57 mm
Ports & interfaces		Depth	21 mm
Ethernet LAN (RJ-45) ports	3	Height	91 mm
Power over Ethernet (PoE) ports quantity	3	Weight	200 g
Design		Technical details	
Product colour	Black	Sustainability certificates	RoHS
Mounting type	Wall	Compliance certificates	RoHS
LED indicators	PoE, Power	Packaging content	
Country of origin	Taiwan	Quick start guide	✓
Certification	FCC Part 15, Class B, CE	Packaging data	
Power		Package type	Box
Power consumption (max)	2.5 W	Package width	93 mm
Power over Ethernet (PoE)	✓	Package depth	43 mm
Power over Ethernet (PoE) voltage range	46 - 57 V	Package height	140 mm
Operational conditions		Package weight	100 g
Operating temperature (T-T)	0 - 50 °C	Logistics data	
		Harmonized System (HS) code	85176990



4015867191286

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.