

QNAP TVS-672X-I3-8G/6TB-EXOS NAS/storage server Tower Ethernet LAN Black i3-8100T





Brand: QNAP Product code: TVS-672X-I3-8G/6TB-EXOS

Product name: TVS-672X-I3-8G/6TB-EXOS

- 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization, intensive file access, large backup/restoration tasks, and media transfer
- Dual M.2 PCIe Gen 3 x2 NVMe SSD slots enable cache acceleration or SSD storage pools for improved performance
- PCIe expansion allows for 2.5/5/10/25GbE network cards, QM2 card, QXP storage expansion cards, or graphics cards
- 4K media playback and real-time transcoding; display multimedia content saved on the NAS via HDMI 2.0 (4K @60Hz) output
- Host multiple virtual machines and containers to run a wide range of applications and services
- A business-class backup center supporting backup/restore of cloud data and VMs (including Google™ Workspace, Microsoft 365®, VMware® and Hyper-V)

Intel Core i3-8100T (4x 3.1GHz), Intel UHD Graphics 630, 8GB DDR4, 5GB Flash, 6x 2.5"/3.5" SATA, 2x M.2, LAN, HDMI, USB, LCD

| Storage | | Performance | |
|---|--------------------------------------|--------------------------------------|--|
| Storage drive interface * | Serial ATA II, Serial ATA III | Device class * | Small & Medium Business |
| Supported storage drive interfaces | M.2, Serial ATA II, Serial ATA III | Backup function * | ✓ |
| Storage drive sizes supported | 2.5,3.5,M.2 | Backup features | Cloud, USB drive, iSCSI LUN |
| Number of M.2 (M & B) slots | 2 | Buzzer | ✓ |
| RAID support * | ✓ | Multilingual support | ✓ |
| RAID levels | 0, 1, 5, 6, 10, 50, JBOD | Number of users | 4096 user(s) |
| Online RAID migration | ✓ | Noise level | 23.8 dB |
| Online RAID expansion | ✓ | Third-party support | ✓ |
| RAID rebuild | ✓ | Snapshot | ✓ |
| Hot-swap drive bays | ✓ | Web-based management | ✓ |
| Supported file systems | FAT32, HFS+, NTFS, exFAT, ext3, ext4 | Share folder access right management | ✓ |
| Storage drives installed * | ✓ | | 256-bit AES, FIPS 140-2, HTTPS, |
| Total installed storage capacity * | 6 TB | Security algorithms | SNMPv2, SNMPv3, SSH, SSL/TLS, |
| Number of storage drives installed * | 6 | Access Control List (ACL) | TLS |
| Number of storage drives supported | 6 | Access Control List (ACL) | √ |
| * | · · | Reset button | √ |
| Installed storage drive type * | HDD | On/off switch | √ |
| Supported storage drive types * | HDD & SSD | Built-in BitTorrent client | V |
| Bad block scan | ✓ | Built-in UPnP AV media server | √ |
| Disk roaming | ✓ | Built-in FTP server | Martin Flactor Missaudi Falsa |
| Processor | | Browser supported | Mozilla Firefox, Microsoft Edge, Google Chrome, Apple Safari |
| Processor manufacturer * | Intel | System log | ✓ |
| Processor generation | 8th gen Intel® Core™ i3 | Hot spare | ✓ |
| Processor family * | Intel® Core™ i3 | Password authentication | ✓ |
| Processor model * | i3-8100T | Disk scan | ✓ |
| Processor frequency * | 3.1 GHz | S.M.A.R.T. support | ✓ |
| Processor cores | 4 | Remotely operated | ✓ |
| Processor threads | 4 | USB copy function | ✓ |
| Bus type | DMI3 | Software | |
| Configurable TDP-down frequency | 2.4 GHz | Operating system installed * | QNAP Turbo System |
| CPU configuration (max) | 1 | Operating system version | 4.5.1 |
| Number of processors supported On-board graphics card model | 1 Intel® UHD Graphics 630 | Windows operating systems supported | Windows 10, Windows 7, Windows |
| Memory | | Linux operating systems supported | ✓ |
| Internal memory type | DDR4 | Mac operating systems supported | ✓ |
| Maximum RAM supported Memory slots Internal memory * | 64 GB 2 8 GB | Server operating systems supported | Windows Server 2008 R2, Window Server 2012, Windows Server 2013 R2, Windows Server 2016, Window Server 2019 |

| Memory | | Power | |
|---|--|--|--|
| Memory form factor Flash memory | SO-DIMM 5000 MB | Power supply location Power supply unit (PSU) capacity | Built-in 250 W |
| Network | | Number of power supply units | 1 |
| Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) | 100,1000,2500,5000,10000 Mbit/s 10000 Mbit/s | Power consumption (typical) Power consumption (HDD standby) AC input voltage Fan voltage | 45.6 W 26.52 W 100 - 240 V 12 V |
| DHCP client | ✓ | Weight & dimensions | |
| DHCP server | ✓ | Width * | 264.3 mm |
| Jumbo frames support | ✓ | Depth * | 279.6 mm |
| iSCSI support | ✓ | Height * | 188.2 mm |
| Wake-on-LAN ready | ✓ | Packaging content | |
| Link aggregation | ✓ | | AC LAN (DLAF) |
| Load balancing system | ✓ | Cables included | AC, LAN (RJ-45) |
| Dynamic DNS (DDNS) | ✓ | Power cables quantity | 1 |
| WLAN adapter supported | ✓ | Processor special features | |
| Ports & interfaces | | Embedded options available | ✓ |
| USB port * | ✓ | Enhanced Intel SpeedStep Technology | ✓ |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1 | Execute Disable Bit | ✓ |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A | 2 | Idle States | ✓ |
| ports quantity | 2 | Intel 64 | ✓ |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C | 2 | Intel Clear Video Technology | ✓ |
| ports quantity | 1 | Intel Enhanced Halt State | ✓ |
| HDMI ports quantity HDMI version | 1 2.0 | Intel Identity Protection Technology version | 1.00 |
| Ethernet LAN (RJ-45) ports * | 3 | Intel Secure Key Technology version | 1.00 |
| PCI Express x4 (Gen 3.x) slots | 1 | Intel Stable Image Platform Program (SIPP) | × |
| Design Chassis type * | Tower | Intel Stable Image Platform Program (SIPP) version | 0.00 |
| Cooling type * | Active | Intel Trusted Execution Technology | × |
| Product colour | Black | Intel TSX-NI | × |
| Number of fans | 3 fan(s) | Intel TSX-NI version | 0.00 |
| Fan diameter | 12 cm | Intel Virtualization Technology (VT- | 1 |
| Fan diameter 2 | 6 cm | x) | • |
| Drive bay locking | × | Intel Virtualization Technology for Directed I/O (VT-d) | ✓ |
| LED indicators | ✓ | Intel VT-x with Extended Page | |
| Built-in display | ✓ | Tables (EPT) | ✓ |
| Display type | LCD | Operational conditions | |
| Cable lock slot | V. | Operating temperature (T-T) | 0 - 40 °C |
| Cable lock slot type | Kensington | Operating relative humidity (H-H) | 5 - 95% |
| Performance | | Storage temperature (T-T) | -20 - 70 °C |
| Type * | NAS | Storage relative humidity (H-H) | 5 - 95% |

