QNAP

QNAP TS-1232XU-RP NAS Rack (2U) Annapurna Labs Alpine AL-324 4 GB DDR4 120 TB HDD QNAP Turbo System Black

Brand : QNAP **Product code:** TS-1232XU-RP-4G-120TB-GLD

Product name: TS-1232XU-RP

Ethernet LAN data rates

2U, 12-Bay, Alpine AL-324, Quad-Core, 1.7GHz, 64-bit, 4 GB DDR4, 512MB DOM, 2.5", 3.5", SATA III, RJ-45, SFP+, USB 3.0, PCIe 2.0x2,, 13kg, PSU ATX 250W, 120TB (WD Gold)
QNAP TS-1232XU-RP. Type: NAS. Chassis type: Rack (2U). Device class: Large Enterprise Business.
Processor family: Annapurna Labs, Processor model: Alpine AL-324, Processor frequency: 1.7 GHz.
Internal memory: 4 GB, Internal memory type: DDR4. Total installed storage capacity: 120 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System



Storage		Design	
Storage drive capacity * Storage drive interface * Supported storage drive interfaces Storage drive size Storage drive sizes supported RAID support *	10 TB Serial ATA III Serial ATA III 2.5/3.5" 2.5,3.5" ✓	Number of fans Fan diameter Fan diameter 2 LED indicators Cable lock slot Cable lock slot type	2 fan(s) 7 cm 7 cm HDD, LAN, Power, Status ✓ Kensington
RAID levels	0, 1, 5, 6, 10, JBOD	<i>3.</i>	Kensington
Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types *	✓ ✓ ✓ FAT32, HFS+, NTFS, exFAT, ext3, ext4 ✓ 120 TB 12	Performance Type * Device class * Backup function * Backup features Buzzer Noise level Snapshot Web-based management Security algorithms Access Control List (ACL) Reset button On/off switch	NAS Large Enterprise Business Cloud, iSCSI LUN 31.7 dB 256-bit AES, HTTPS, SSH
Bad block scan	✓	Built-in iTunes server	✓
Processor Processor family * Processor model *	Annapurna Labs Alpine AL-324	Built-in FTP server Browser supported	Apple Safari 7, Google Chrome, Microsoft Internet Explorer 10, Mozilla Firefox
Processor frequency * Processor cores Processor architecture PCI Express configurations PCI Express slots version Processor operating modes	1.7 GHz 4 ARM Cortex-A57 2x2 2.0 64-bit	System log Hot spare Password authentication S.M.A.R.T. support Universal Plug and Play (UPnP) Software	WIDZIII ATTIETOX
Memory		Operating system installed *	QNAP Turbo System
Internal memory * Internal memory type Maximum RAM supported Memory slots Flash memory	4 GB DDR4 16 GB 1 512 MB	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported	QNAP Turbo System 4.3.4 Windows 10, Windows 7, Windows 8 ✓ Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9
Network		nae operating systems supported	Mavericks
Ethernet LAN *	✓		

10,100,1000 Mbit/s

Network		Software	
Ethernet LAN data rate supported (max) Wi-Fi DHCP client DHCP server	·	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
	1	Power	
Jumbo frames support iSCSI support Wake-on-LAN ready Dynamic DNS (DDNS)	* * * * * * * * * *	Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS)	Built-in 250 W 2
Ports & interfaces	•	support AC input voltage	√ 100 - 240 V
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	√ 4 2	AC input frequency Fan voltage Output current	50 - 60 Hz 12 V 3.5 A
Fiber optic connector	SFP+	Weight & dimensions	
Ethernet LAN (RJ-45) ports *	2	Width *	482 mm
Cooling type * Ac	Rack (2U) Active Black	Depth * Height * Weight	534 mm 89 mm 13 kg
		Packaging content	
		Cables included Quick installation guide Number of screws	AC, LAN (RJ-45) ✓ 84
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

