QNAP TS-432PXU-2G NAS Rack (1U) Annapurna Labs Alpine AL-324 2 GB DDR4 8 TB HDD Black

Brand : QNAP

Product code: TS-432PXU-2G/8TB-REDPLUS



Product name : TS-432PXU-2G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing

- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning

- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google $^{\rm m}$ G Suite and Microsoft 365 \circledast

- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

- Expand the application potential of the TS-432PXU by installing a compatible PCIe card

- Increase the storage capacity of the TS-432PXU with QNAP TR RAID expansion enclosures or TL JBOD

4x 3.5", 2GB DDR3, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 250W PSU, 44x439x499 mm

| Storage | | Design | |
|---|--|--|---|
| Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types * | 2.5,3.5" 0, 1, 5, 6, 10, JBOD FAT32, HFS+, NTFS, ext3, ext4 8 TB 4 HDD HDD & SSD | Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators Performance | Rack (1U) Active Black 2 fan(s) 4 cm HDD, LAN, Status |
| | | Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Web-based management | NAS Small & Medium Business ✓ Cloud, iSCSI LUN ✓ ✓ ✓ Z56-bit AES, FIPS 140-2, HTTPS, |
| Bad block scan Processor | 4 | Security algorithms | SSH, SSL/TLS |
| Processor manufacturer * Processor family * Processor model * Processor frequency * Processor cores | Annapurna Labs Annapurna Labs Alpine AL-324 1.7 GHz 4 | Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported | Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+, |
| Memory | | System log | Google Chrome |
| Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor | 2 GB DDR4 16 GB 1 UDIMM | Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) USB copy function | ✓ CIFS/SMB ✓ |
| Flash memory | 512 MB | Software | |
| Network Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) DHCP client DHCP server Jumbo frames support iSCSI support | 100,1000,2500,10000 Mbit/s 10000 Mbit/s | Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported | 4.4.3 Windows 10, Windows 7, Windows 8 ✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina |

| Network | | Software | |
|--|---------------------------------------|---|--|
| Wake-on-LAN ready Supported network protocols Link aggregation | ✓ PPTP, L2TP/IPSec, OpenVPN, QBelt | Server operating systems supported | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 |
| Load balancing system WLAN adapter supported | | Power | |
| Ports & interfaces | | Power supply location Power supply unit (PSU) capacity | Built-in 250 W |
| USB port * | < | Number of power supply units | 1 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 | AC input voltage | 100 - 240 V |
| Fiber ports quantity | 2 | Fan voltage | 12 V |
| Fiber optic connector | SFP+ | Weight & dimensions | |
| Ethernet LAN (RJ-45) ports * | 2 | Width * | 439 mm |
| | | Depth * | 499 mm |
| | | Height * | 44 mm |
| | | Weight | 6.53 kg |

Packaging content Cables included

Number of screws

Operational conditions Operating temperature (T-T)

Operating relative humidity (H-H)

AC, LAN (RJ-45)

28

0 - 40 °C

5 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.