QNAP TS-863XU-RP NAS Rack (2U) AMD G GX-420MC 4 GB DDR3L 64 TB HDD QNAP Turbo System Black

Brand : QNAP

Product code: TS-863XU-RP-4G-64TB-GLD



- Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing

- Qtier auto-tiering technology and SSD caching enable constant storage optimization

- Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks

- Host containerized applications and virtual machines with various operating systems

- Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery

- NAS and iSCSI-SAN (IP-SAN) unified storage solution with scalable design

AMD G-Series GX-420MC 2.0 GHz, 4 GB DDR3L, 512MB DOM, 8x 2.5"/3.5" SATA III, 2x USB 3.0, 2x USB

2.0, 1x PCIe 2.0 x4, 1x RJ-45 10GBASE-T, 4x 1G RJ-45, 2U, 89x482x534 mm





Storage		Design	
Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels	Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, 50, 60, JBOD	Fan diameter LED indicators Cable lock slot Cable lock slot type	7 cm HDD, LAN, USB ✓ Kensington
RAID levels Online RAID migration Online RAID expansion Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types * Bad block scan Processor Processor family *	0, 1, 5, 6, 10, 50, 60, JBOD ✓ ✓ FAT32, HFS+, NTFS, ext3, ext4 ✓ 64 TB 8 HDD HDD & SSD ✓ AMD G	Performance Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Web-based management Share folder access right management Security algorithms	NAS Small & Medium Business Cloud, iSCSI LUN 36.4 dB 256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Processor model * Processor frequency * Processor cores	GX-420MC 2 GHz 4	Access Control List (ACL) Reset button On/off switch	✓ ✓ ✓ Safari 7+, Chrome, Internet
Memory Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Elash memory	4 GB DDR3L 16 GB 2 SO-DIMM 512 MB	Browser supported System log Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP)	Explorer 10+, Firefox CIFS/SMB
Flash memory Network	212 MB	Software	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) Copper ethernet cabling technology Wi-Fi DHCP client Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols	 10,100,1000,10000 Mbit/s 10000 Mbit/s 10GBASE-T, 1000BASE-T <!--</td--><td>Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported</td><td>QNAP Turbo System 4.3.4 Windows 10, Windows 7, Windows 8 ✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks</td>	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported	QNAP Turbo System 4.3.4 Windows 10, Windows 7, Windows 8 ✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks

Ports & interfaces		Software	
USB port * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	✓ 2 2	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Ethernet LAN (RJ-45) ports *	5	Power	
Cooling type * Product colour	Rack (2U) Active Black 2 fan(s)	Power supply location Power supply unit (PSU) capacity Number of power supply units AC input voltage Fan voltage	Built-in 250 W 2 100 - 240 V 12 V
		Weight & dimensions	
		Width *	482 mm
		Depth *	534 mm
		Height *	89 mm

Packaging content Cables included

Quick installation guide

Operational conditions Operating temperature (T-T)

Operating relative humidity (H-H)

AC, LAN (RJ-45)

∢

0 - 40 °C

5 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.