



TVS-h874T-i9-64G	
CPU	Intel® Core™ i9 16-core (8P+8E) /24-thread Processor
CPU Architecture	64-bit x86
Graphic Processors	Intel® UHD Graphics 770
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
Hardware-accelerated Transcoding	Yes
System Memory	64 GB SODIMM DDR4 (2 x 32 GB)
Maximum Memory	64 GB (2 x 32 GB)
Memory Slot	2 x SODIMM DDR4
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	8 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
M.2 Slot	2 x M.2 2280 PCIe Gen 4 x4 slots
	Compatible with NVMe SSD PCIe Gen 3 and above. Please refer to https://www.qnap.com/compatibility/ for compatibility.
SSD Cache Acceleration Support	Yes
GPU pass-through	Yes
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (2.5G/1G/100M/10M)
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes

Thunderbolt Port 2 (Thunderbolt™ 4) Supports only Thunderbolt connections for Windows & Mac hosts ar devices. Third-party Thunderbolt external storage devices are not support of the party of the party Thunderbolt external storage devices are not support of the party of the p	pported.
devices. Third-party Thunderbolt external storage devices are not support of the property of	pported.
Slot 1: PCIe Gen 4 x16 Slot 2: PCIe Gen 4 x4 *Slot 2 is preinstalled with a Thunderbolt 4 AIC. Card dimensions for PCIe slot 1~Slot 2 : 185 x 131.15 x 18.76 mm / 7 inches. Wider cards can be installed if the next PCIe slot will not be used. USB 3.2 Gen 2 (10Gbps) Port 1 x Type-C USB 3.2 Gen 2 10Gbps 2 x Type-A USB 3.2 Gen 2 10Gbps 1 x Type-A USB 3.2 Gen 2 10Gbps 1 x Type-A USB 3.2 Gen 2 10Gbps Tompian 1.4b (up to 4096 x 2160 @ 30Hz) Form Factor Tower LED Indicators HDD 1-8, Status, LAN, USB port, M.2 port LCD Display/ Button Yes Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	.28 x 5.16 x 0.74
Card dimensions for PCIe slot 1~Slot 2: 185 x 131.15 x 18.76 mm / 7 inches. Wider cards can be installed if the next PCIe slot will not be used. USB 3.2 Gen 2 (10Gbps) Port 1 x Type-C USB 3.2 Gen 2 10Gbps 2 x Type-A USB 3.2 Gen 2 10Gbps 1, HDMI™ 1.4b (up to 4096 x 2160 @ 30Hz) Form Factor Tower LED Indicators HDD 1-8, Status, LAN, USB port, M.2 port LCD Display/ Button Yes Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	.28 x 5.16 x 0.74
Port 2 x Type-A USB 3.2 Gen 2 10Gbps HDMI™ Output 1, HDMI™ 1.4b (up to 4096 x 2160 @ 30Hz) Form Factor Tower LED Indicators HDD 1-8, Status, LAN, USB port, M.2 port LCD Display/ Button Yes Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	
Form Factor Tower LED Indicators HDD 1-8, Status, LAN, USB port, M.2 port LCD Display/ Button Yes Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	
LED Indicators HDD 1-8, Status, LAN, USB port, M.2 port LCD Display/ Button Yes Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	
LCD Display/ Button Yes Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	
Buttons Power, Reset, USB Copy Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	
Dimensions (HxWxD) 180.2 × 329.3 × 279.6 mm	
Dimensions do not include foot pad (foot pad may be up to 30mm / depending on model)	1.18 inches high
Weight (Net) 7.34 kg	
Weight (Gross) 8.99 kg	
Operating Temperature 0 - 40 °C (32°F - 104°F)	
Storage Temperature -20 - 70°C (-4°F - 158°F)	
Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C (80.6°F)	
Power Supply Unit 350W (PWR-PSU-350W-DT01), 100-240V	
Power Consumption: 62.668 W HDD Sleep Mode	
Power Consumption: 104.35 W	
Operating Mode, Typical Tested fully populated with WD10EFRX hard drives.	
Fan System fan: 2 x 120mm, 12VDC CPU fan: 1 x 60mm, 12VDC	
System Warning Buzzer	
Kensington Security Slot Yes	

Max. Number of 3500 Concurrent Connections (CIFS) - with Max. Memory

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.