



# HSM SECURIO B32 - 1 x 5 mm




## HSM SECURIO B32 document shredder

High quality materials, proven quality – the reliable security partner in the workplace. With an intake width of 310 mm, the document shredder effortlessly shreds DIN A3 paper. It is the perfect device for working groups.

### Technical data

<b>Order number:</b>	1824811	<b>Intake width:</b>	310 mm
<b>EAN</b>	4026631032636	<b>Container volume / collecting:</b>	82 l
<b>Cutting type:</b>	particle cut	<b>Collection volume in sheets (80 g):</b>	1508
<b>Cutting size:</b>	1 x 5 mm	<b>Noise level (idle operation):</b>	ca. 56 dB(A)
<b>Security level (DIN 66399):</b>	F-3   P-7	<b>Width x Depth x Height:</b>	497 x 398 x 793 mm
<b>Cutting capacity in sheets 80g/m<sup>2</sup>:</b>	4	<b>Weight:</b>	27 kg
<b>Power consumption:</b>	500 W	<b>Shredder material:</b>	Paper
<b>Voltage / Frequency:</b>	230 V / 50 Hz		

### Product information



The induction-hardened, solid steel cutting rollers guarantee durability.



The full bin is indicated via the display and the machine switches off automatically.



The device can be intuitively operated with the multifunction element.

# HSM®



### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



### Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



### High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



### Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.




### Display bin full

The full bin is indicated via the display and the machine switches off automatically.



### Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.



Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



\*HSM SECURIO B24, B26, B32

[www.hsm.eu](http://www.hsm.eu)

# HSM®