

Cat6 Patch Cable - Unshielded U/UTP Copper

Network



Features:

Category:	Cat6
Frequency:	250 Mhz
Impedance:	100 Ohms
Conductor:	Copper
Wiring Standard:	ANSI/TIA 568C.2 - ISO 11801
Jacket Material:	PVC
Packaging:	Separate Packs

▶ [View Range](#)



WHITE

BLACK

BLUE

GREEN

GREY

RED

YELLOW

	WHITE	BLACK	BLUE	GREEN	GREY	RED	YELLOW
0.15m							
0.3m							
0.5m	246782-HY	246771-HY	246700-HY	244700-HY	848050-HY	243700-HY	245700-HY
0.7m							
1.0m	246783-HY	246772-HY	246710-HY	244710-HY	848100-HY	243710-HY	245710-HY
1.5m	246784-HY	246773-HY	246740-HY	244740-HY	240960-HY	243740-HY	245740-HY
2.0m	246785-HY	246774-HY	246720-HY	244720-HY	848200-HY	243720-HY	245720-HY
3.0m	246786-HY	246775-HY	246730-HY	244730-HY	848300-HY	243730-HY	245730-HY
5.0m	246787-HY	246776-HY	246750-HY	244750-HY	848500-HY	243750-HY	245750-HY
7.0m	246788-HY	246777-HY	246770-HY	244770-HY	240670-HY	243770-HY	245770-HY
10.0m	246789-HY	246778-HY	246760-HY	244760-HY	848101-HY	243760-HY	245760-HY
15.0m	246790-HY	246779-HY	246761-HY	244761-HY	848915-HY	243761-HY	245761-HY
20.0m	246791-HY	246780-HY	246762-HY	244762-HY	848920-HY	243762-HY	245762-HY
25.0m	246792-HY	246781-HY	246763-HY	244763-HY	240850-HY	243763-HY	245763-HY
30.0m					848930-HY		
50.0m					240950-HY		

ProConnectLite®

All Hypertec ProConnectLite® products come with Lifetime Warranty and Free UK, Pre and Post Sale Technical Support. Our team of Connectivity Experts are also on hand to help assist with any Cabling and Connectivity requirements, please email proconnect@hypertec.co.uk.