

### Cat6 Patch Cable - Outdoor F/UTP Copper

### Network



#### Features:

Category:	Cat6
Frequency:	250 Mhz
Impedance:	100 Ohms
Conductor:	Copper
Shielding:	Collectively shielded with aluminium foil
Wiring Standard:	ANSI/TIA 568C.2 - ISO 11801
Jacket Material:	PVC + PE (Anti UV Polyethylene)
Packaging:	Seperate Packs

▶ [View Range](#)



LENGTH	BLACK
0.5m	845038-HY
1.0m	845039-HY
2.0m	845040-HY
3.0m	845041-HY
5.0m	845042-HY
7.5m	845043-HY
10.0m	845044-HY
15.0m	845045-HY
20.0m	845046-HY
25.0m	845047-HY
30.0m	845048-HY
40.0m	845049-HY
50.0m	845050-HY



Need Help? Speak to a Hypertec  
Connectivity Expert.  
**01488 686 844**  
[proconnect@hypertec.co.uk](mailto:proconnect@hypertec.co.uk)

#### ProConnectLite®

All Hypertec ProConnectLite® products come with Lifetime Warranty and Free UK, Pre and Post Sale Technical Support. Our team of Connectivity Experts are also on hand to help assist with any Cabling and Connectivity requirements, please email [proconnect@hypertec.co.uk](mailto:proconnect@hypertec.co.uk).