



VDS-1202 Version: 1

Ethernet over VDSL2 Converter, Annex B

Why convert Ethernet to VDSL? The LevelOne VDS-1202 converts your data from Ethernet to VDSL, making it easy to send high-bandwidth data over long distances. This new technology uses traditional twisted-pair telephone wiring instead of expensive Cat.5 cables.

New technology = cost-effective deployment When using VDSL2 (Very High Speed Digital Subscriber Line) technology, users can transmit data up to 250 meters without having to add expensive Ethernet switches or cables to extend the network reach. And with 100Mbps downstream and 100Mbps upstream, VDSL2 technology provides ample space for all high bandwidth usage.

Fast transfer speeds? Yes. Easy Installation? Yes. VDS-1202 works especially well in applications where traditional copper phone lines are already installed: apartments, condominiums, hotels, university campus, etc. There is no need to run expensive Ethernet cables and installers can easily integrate VDSL technology into the existing network. The VDS-1202 is plug and play ready and requires minimum installation time.

Customized settings Each VDS-1202 also allows for customized settings for advanced use. Using a built-in DIP switch, users can customize the behavior of the device to match the desired network configuration.

Annex B For networks that utilize ISDN telephone systems.

Key Features

- Trellis coding support up to 1024 discrete multi-tone bins and 4 Dip Switches for configuration settings
- Low-Latency for Video/Voice/Data applications
- Supports a VDSL connection of up to 2km over single pair copper wire
- Features selectable Fast and Interleaved modes
- Selectable fixed data rate and fixed SNR margin

Specifications

System Specifications

Standards & Protocols:

VDSL2:

ITU-T G.993.2

Supports VDSL2 profiles :17a, 30a

Max Data Rate: 100/100 Mbps

POTS:

Annex B

LAN:
www.level1.com

Auto-Detection for 10/100 BaseT and Half/Full duplex



High performance bridge for Ethernet extension
Fully compatible with IEEE802.3/IEEE802.3u
Automatic MDI/MDIX Function

Port:

2 x RJ45 Ethernet port
1 x RJ11 DSL Interfaces

Indicator:

POWER(Power is ON/OFF)
LAN1(Data Activity/Link)
LAN2(Data Activity/Link)
DSL(VDSL Loop Connection Status)
M/S(Master/Slave Selection)

Power Input:

DC 12V/1A

Operating Temperature (°C):

0 ~ 40 degree C

Operating Humidity (Non-condensing):

5% to 95% non-condensing

Features

General:

1. ITU-T G.993.1, G.993.2 VDSL/VDSL2 and SG15Q4 DMT Compliance
2. 100/100Mbps Down/Up Stream for distance up to 300 meters
3. Trellis Coding support up to 1024 Discrete Multi-Tone (DMT) bin
4. Supports DSL connection up to 1500 meters
5. Selectable fixed SNR margin
6. Auto MDIX for 10/100 BaseT Ethernet LAN Ports
7. 4 Dip Switches for Master/Slave Configurations
8. Low-Latency for Video/Voice/Data applications

Performance

Operating Distance:

ITU-T G.993.1/2, SG15Q4 DMT Compliance
Trellis Code with 1024 DMT bins
Max Data Rate: 100/100 Mbps

Physical Specifications

Dimensions (W x D x H mm):

120 x 90 x 28 (mm)

Weight (g):

330

Approval and Compliance

EMI/EMS:

CE, FCC, LVD, JATE

Order Information

VDS-1202

Package Contents

VDS-1202

Power Adapter

Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.