



QSW-2104-2S

| | |
|--|---|
| Management Type | Unmanaged |
| Number of Ports | 6 |
| 10GbE SFP+ | 2 |
| 2.5GbE (RJ45) | 4 |
| Power Supply Description | Adapter |
| Max. Power Consumption | 12W |
| Input Power Type | DC |
| Input Voltage Range | 12V/1A |
| MAC Address Table | 16K |
| Total Non-Blocking Throughput | 30Gbps |
| Switching Capacity | 60Gbps |
| Energy Efficient Ethernet (IEEE 802.3az complaint) | Yes |
| Fanless | Yes |
| Supported Standards | IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000BASE-T Gigabit Ethernet IEEE 802.3bz 2.5G/5GBase-T IEEE 802.3an 10GBase-T IEEE 802.3az Energy Efficient Ethernet (EEE)IEEE SFP Transceiver 1000BASE-SX SFP Transceiver 1000BASE-LX SFP Transceiver 1000BASE-T Copper RJ45 GBIC |
| Form Factor | Desktop |
| LED Indicators | Per Port: Speed/Link/Activity Loop LED: Loop Per System: Power/Status |
| Dimensions (HxWxD) | 34 x 180 x145 mm |

| | |
|----------------------------|----------------------------------|
| Weight (Net) | 0.713 kg |
| Weight (Gross) | 1.01 kg |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Relative Humidity | 5~90% Non-condensing |
| Certifications | FCC, CE, BSMI, VCCI, LVD,CCC,KCC |
| Electromagnetic Compliance | Class B |
| Jumbo Frames | 9K |
| Warranty | 2 Years |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.