

## ProDockLite®

Universal USB 3.1 Type C Mini Dock



**Connect USB-C Laptops, Ultrabooks & Devices to Displays, Projectors, Networks, and other Peripherals with ease!**

### Features:

- ✓ Universal USB 3.1 Type-C Connection
- ✓ HDMI® Supports 4K Ultra-HD Video
- ✓ 1080p VGA Support
- ✓ 2 x USB 3.0 Ports
- ✓ RJ45 Gigabit Ethernet
- ✓ SD Card Reader (Also reads MicroSD)
- ✓ 3.5mm Audio Output
- ✓ 100W Power Delivery via Type-C Port
- ✓ Windows & MAC compatible

### Turn your USB-C Laptop into the Ultimate Hub

The ProDockLite® Dock from Hypertec enables mobile workers with USB-C Laptops, Tablets or Ultrabooks to connect to a variety of peripherals in the office or at home. Taking full advantage of the latest USB 3.1 Specification, the ProDockLite is capable of delivering high quality video, fast file transfer speeds and 100W power delivery from a single Type-C connection.

### Empower your Workflow, Wherever you are

The ProDockLite® also features a USB 3.1 Type C female port that allows users to power their USB-C Laptop or Ultrabook while connected. With an ultra-portable design, the ProDockLite® is ideal for hot desk applications and mobile work environments.

Part Code: **HYP-USBCPD-L2**





SD Card  
TF MicroSD




USB-C 100W  
Charging Port



3.5mm Audio/  
Headphones



USB 3.0  
Storage & Flash Drives  
Device Charge & Sync  
Peripherals



1080p  
VGA



Compatibility Tested with:

- ✓ ASUS ZenBook3U
- ✓ DELL XPS13
- ✓ DELL Alienware 13 R2
- ✓ HP Spectre Notebook
- ✓ HUWAEI MateBook
- ✓ Lenovo ThinkPad X1 Carbon 5
- ✓ Macbook 8/ 9/ 10
- ✓ Macbook Pro 13/ 14/ 15
- ✓ iMac 18
- ✓ Xiami Air 13
- ✓ HTC 10
- ✓ LG G5
- ✓ HUAWEI P20Pro
- ✓ Samsung S8

Part Code:  
HYP-USBCPD-L2

RoHS compliant.

## Additional Technical Information

### USB

100W power delivery Type- C Port supports 20V 5A power charging for your USB-C Device.

2x USB 3.0 ports support up to 5Gbps data transfer and other standard USB devices (Keyboards/ Mice/ USB Flash/ Hard Disks/ etc).

Support power outputs up to 900mA from USB ports.

### Audio & Video

HDMI port supports up to max video resolution up to 4K\*2K@30Hz. Both video and audio support.

VGA port supports up to max video resolution up to 1920\*1080p@60Hz. It can support sound output by plugging a 3.5mm Audio cable at the back side of the dock.

Single video only- this dock does not support simultaneous VGA and HDMI display output.

### Network & Other

Can support Gigabit Ethernet and does not require CD Driver when you set up (disc free).

SD Card Reader supports SD card and Micro SD card (TF card). Maximum read and write is 60Mbps.

For more information on the **ProDockLite**<sup>®</sup>, speak to a Hypertec Account Manager today.